



Optomechanics for quantum technologies

Shabir Barzanjeh¹✉, André Xuereb²✉, Simon Gröblacher³, Mauro Paternostro⁴, Cindy A. Regal^{5,6} and Eva M. Weig^{7,8,9}

The ability to control the motion of mechanical systems through interaction with light has opened the door to a plethora of applications in fundamental and applied physics. With experiments routinely reaching the quantum regime, the focus has now turned towards creating and exploiting interesting non-classical states of motion and entanglement in optomechanical systems. Quantumness has also shifted from being the very reason why experiments are constructed to becoming a resource for the investigation of fundamental physics and the creation of quantum technologies. Here, by focusing on opto- and electromechanical platforms we review recent progress in quantum state preparation and entanglement of mechanical systems, together with applications to signal processing and transduction, quantum sensing and topological physics, as well as small-scale thermodynamics.

Optomechanics traces its origins to well over a century ago¹. In 1917, Einstein famously discussed how photons transfer momentum to mirrors²; even further back, by 1619 Kepler had hypothesized that the direction in which comet tails point is partly a result of what we would nowadays term radiation pressure³. In optomechanical systems, momentum is exchanged between electromagnetic radiation and mechanical objects. Progress in manufacturing technology and nanofabrication made it possible, by the first decade of this century⁴, to start working towards bringing mechanical systems to the quantum regime—close to their quantum ground state, where the quantization of energy levels and the uncertainty principle have a marked effect on their dynamics. The potential for optomechanical device fabrication to build on standard microchip technology provides a unique degree of integrability, controllability and scalability. These fabrication techniques make it possible to couple mechanical resonators to electromagnetic radiation by embedding nano- or microscale mechanical resonators in optical cavities^{5,6} or superconducting microwave circuits^{7–9}. This helps to bring optomechanical systems to the fore as candidates for future quantum technologies.

The emergence of quantum technologies relies on the capability of controlling quantum devices and of tailoring their mutual, quantum-coherent, interaction¹⁰. Mechanical motion is capable of coupling to a wide variety of natural (for example, photons) or engineered^{11,12} (for example, artificial atoms) quantum systems. Moreover, the physical properties of fabricated mechanical devices, in contrast to those of natural quantum systems, can be designed as desired. The ability to bring mechanical systems to the quantum regime and controlling their quantum state paves the way to the building up of a veritable quantum toolbox based on mechanical motion. As discussed by Braginskii and colleagues in the late 1960s¹³, optomechanical interactions are intimately connected with the quantum-limited measurement¹⁴ of physical phenomena. Beyond being quantum probes useful to measure classical quantities, optomechanical systems are also applicable to

measuring genuine quantum phenomena. Recent developments have exploited this ability to create and observe non-classical correlations, including Hanbury Brown–Twiss correlations¹⁵ of individual phonons and entanglement¹⁶ between two mechanical resonators, and to test Bell non-locality¹⁷ with nano- or microscale mechanical resonators.

In this Review we present an overview of recent progress in optomechanical systems and their technological applications. Our discussion will cover various mechanical systems interacting with electromagnetic radiation in the microwave or optical region of the spectrum; we refer to all of these platforms as optomechanical systems. The investigation of non-classical correlations and entanglement between mechanical systems and optical or microwave fields, or between pairs of mechanical systems, is of much interest because it connects quantum physics and tangible objects. Advances in optomechanical systems have motivated their use in applications such as quantum-coherent transducers between optical and microwave fields^{18,19}, as quantum sensors for displacement and to investigate stochastic and quantum thermodynamics^{20,21}, including as micro- or nanoscopic heat engines and as probes for thermodynamic properties of small-scale systems; this provides one pathway towards autonomous quantum heat engines²² that exploit, for example, mechanical quantization or non-classical correlations. As a final application, we will discuss using optomechanical systems as a platform that employs topological protection for the processing and routing of quantum signals.

Mechanical systems in the quantum regime

Our discussion in this Review will focus mainly on optomechanical devices where a mechanical resonator is coupled to a resonant electromagnetic cavity. Although it is by no means a limitation inherent in the physics of optomechanical systems^{23,24}, the strength of the radiation pressure interaction is typically much greater in cavity optomechanical systems than in free-space devices, making them more technologically relevant. Box 1 gives a brief overview of the

¹Institute for Quantum Science and Technology, University of Calgary, Calgary, Alberta, Canada. ²Department of Physics, University of Malta, Msida, Malta. ³Kavli Institute of Nanoscience, Department of Quantum Nanoscience, Delft University of Technology, Delft, The Netherlands. ⁴Centre for Theoretical Atomic, Molecular, and Optical Physics (CTAMOP), School of Mathematics and Physics, Queen's University, Belfast, UK. ⁵JILA, University of Colorado and National Institute of Standards and Technology, Boulder, CO, USA. ⁶Department of Physics, University of Colorado, Boulder, CO, USA. ⁷Department of Physics, University of Konstanz, Konstanz, Germany. ⁸Department of Electrical and Computer Engineering, Technical University of Munich, Munich, Germany. ⁹Munich Center for Quantum Science and Technology (MCQST), Munich, Germany. ✉e-mail: shabir.barzanjeh@ucalgary.ca; andre.xuereb@um.edu.mt

Box 1 | The optomechanical interaction

A mechanical resonator oscillating at ω_m coupled to an optical cavity resonant at ω_c is described by the Hamiltonian^{4,147}

$$\hat{H}_{\text{OM}} = \hbar\omega_m \hat{b}^\dagger \hat{b} + \hbar\omega_c \hat{c}^\dagger \hat{c} + \hbar g_0 (\hat{b} + \hat{b}^\dagger) \hat{c}^\dagger \hat{c} + \hat{H}_d, \quad (1)$$

where \hat{c} and \hat{b} are the optical and mechanical annihilation operators, respectively. The first two terms are the free Hamiltonians of the mechanical and cavity fields, the third is the dispersive optomechanical coupling with the single-photon optomechanical coupling strength g_0 and $\hat{H}_d = \hbar\mathcal{E}(\hat{c}e^{-i\omega_d t} + \text{h.c.})$ represents the driving of the cavity by a coherent electromagnetic field with frequency ω_d and amplitude \mathcal{E} . Typically, the drive is described by Δ , where $\omega_d = \omega_c + \Delta$; conventionally, $\Delta < 0$ ($\Delta > 0$) is termed red (blue) detuning. In a frame rotating with the driving field, equation (1) transforms to

$$\hat{H}'_{\text{OM}} = \hbar\omega_m \hat{b}^\dagger \hat{b} + \hbar[-\Delta + g_0(\hat{b} + \hat{b}^\dagger)]\hat{c}^\dagger \hat{c} + \hat{H}'_d, \quad (2)$$

where the Hamiltonian associated with the driving field becomes $\hat{H}'_d = \hbar\mathcal{E}(\hat{c} + \hat{c}^\dagger)$. This Hamiltonian is cubic in the field operators and predicts a rich dynamics^{148,149}. In many experiments g_0 is much smaller than the other frequencies involved, leading to a dynamics that can be well approximated by a linearized⁴ Hamiltonian.

We linearize equation (2) by expanding the optical mode around its steady-state amplitude, $\hat{a} = \hat{c} - \alpha$, where $|\alpha|^2 = 4|\mathcal{E}|^2/(\kappa^2 + 4\Delta^2)$ is the mean number of intracavity photons. The linearized Hamiltonian transforms to

$$\hat{H}_{\text{lin}} = -\hbar\Delta\hat{a}^\dagger \hat{a} + \hbar\omega_m \hat{b}^\dagger \hat{b} + \hbar G(\hat{a} + \hat{a}^\dagger)(\hat{b} + \hat{b}^\dagger), \quad (3)$$

where $G = g_0|\alpha|$ is the optomechanical coupling strength; the phase of α does not play a role in the dynamics and can be neglected, but its amplitude acts to amplify the coupling strength. Moving to a frame rotating at the optical and mechanical frequencies, that is, moving to an interaction picture with respect to $-\hbar\Delta\hat{a}^\dagger \hat{a} + \hbar\omega_m \hat{b}^\dagger \hat{b}$, Hamiltonian (3) becomes

$$\hat{H}'_{\text{lin}} = \hbar G(\hat{a}e^{i\Delta t} + \hat{a}^\dagger e^{-i\Delta t})(\hat{b}e^{-i\omega_m t} + \hat{b}^\dagger e^{i\omega_m t}). \quad (4)$$

By properly setting the detuning, the optical and mechanical systems can be made to interact in different ways. If the driving frequency is chosen so that $\Delta = -\omega_m$ and the system is in the sideband-resolved regime, $\omega_m \gg \kappa$, it is possible to use a rotating-wave approximation to drop the rapidly rotating terms oscillating at $\pm 2\omega_m$. This results in an interaction reminiscent of a beam splitter, $\hat{H}_{\text{BS}} = \hbar G(\hat{a}\hat{b}^\dagger + \hat{a}^\dagger \hat{b})$, where excitations are exchanged between photons and phonons at rate G . This type of interaction can be used to cool the mechanical motion to its ground state through sideband cooling, where the mechanical resonator scatters radiation preferentially into resonance with the cavity mode, which lies at a higher frequency than the coherent field that is driving the cavity (Fig. 1b). Setting $\Delta = \omega_m$ results in an interaction of parametric downconversion type, $\hat{H}_{\text{PDC}} = \hbar G(\hat{a}^\dagger \hat{b}^\dagger + \hat{a}\hat{b})$, which generates entanglement between photons and phonons.

theoretical description of a mechanical object interacting with electromagnetic radiation in a cavity⁴; a variety of platforms that have been used to demonstrate or exploit optomechanical physics are illustrated in Fig. 1. In this section, we start by reviewing progress in

cooling mechanical resonators to their motional ground state before discussing the preparation of non-classical states.

Ground-state cooling. The preparation of mechanical harmonic oscillators in the ground (that is, lowest-energy, or vacuum) state of motion was a driving force in optomechanics for nearly a decade⁴. The aim of this quest was to overcome the effects of thermal fluctuations that long precluded study of quantum phenomena in nanomechanical devices. Success in a wide variety of platforms has firmly placed mechanical systems in the quantum regime; this has now become a routine starting point for a variety of complex quantum experiments with mechanical degrees of freedom. High-frequency gigahertz mechanical resonators can be cooled directly to their ground state in a dilution refrigerator. An experiment reporting the use of refrigeration to cool a mechanical resonator to its ground state²⁵ used a superconducting quantum bit (qubit) to read out the mechanical motion of the resonator. This ushered in the study of mechanical elements coupled to qubits in quantum acoustics experiments^{26,27}.

Following this demonstration of reaching the ground state, sideband cooling techniques (Box 1) were used to place the mechanical resonators in electro-²⁸ and optomechanical systems⁵ in their respective ground states. This technique has made possible the study of resonators whose frequency is as low as megahertz²⁹ or below in their quantum ground state; alternative cooling techniques make use of active feedback³⁰ or squeezed light³¹. An attractive feature of optomechanical systems is that the ratio of the strengths of the sidebands that the motion imprints on the outgoing electromagnetic field can be used to determine the absolute temperature of their state of motion³².

While nanofabricated solids were the first mechanical objects to be brought to the ground state, recent years have seen expansion of the platforms for which quantum control is possible, including optically levitated submegahertz mechanical resonators³³, which can be brought into their ground state from room temperature³⁴ or without the use of an optical cavity^{35,36}, optomechanics in superfluid helium coupled to a cavity^{37,38}, and large mass bulk acoustic waves, whose substantial cooling is enabled by large Brillouin couplings³⁹.

Quantum-state preparation of a mechanical resonator. The preparation of non-classical states in optomechanical systems can target two distinct families of states. On the one hand, the dynamics arising from the linearized optomechanical Hamiltonian (3) is limited to the creation of Gaussian states when starting from a thermal state. While manifestly non-classical in a variety of ways, and in fact capable of demonstrating entanglement, Gaussian states can be described by means of a non-negative Wigner quasiprobability distribution⁴⁰ and thus behave somewhat similarly to classical states. On the other hand the full nonlinear optomechanical Hamiltonian becomes important only when the single-photon coupling strength is large. Coupling to a qubit⁴¹, or performing strong measurements⁴², can be used to prepare non-Gaussian states of motion, such as Fock states or Schrödinger cat states⁴³.

A restricted, albeit very important and well studied, class of non-classical states is that of squeezed states, which are intimately tied to a cornerstone of quantum physics, the Heisenberg uncertainty principle. This principle sets the scale of the zero-point fluctuations of a mechanical resonator in its quantum ground state. The optomechanical interaction with combined blue- and red-detuned driving tones (Box 1) allows suppression of one of the quadratures of the mechanical fluctuations below the zero-point level, at the expense of increasing the fluctuations in the orthogonal quadrature. Experimental demonstrations of optomechanical squeezing have been accomplished in electromechanical systems featuring a mechanically compliant, superconducting drum^{7,8,44} or

nanostring^{9,45} parametrically coupled to a microwave cavity like the one shown in Fig. 1e. Evidence of squeezed states of motion of a mechanical resonator is most directly obtained from an analysis of the motional quadrature spectra⁴⁶.

More recently, the strong piezoelectric coupling of superconducting qubits to mechanical resonators²⁵ has grown into the field of quantum acoustics. Systems that strongly couple qubits to mechanical motion enable the counting of phonons in mechanical resonators, placing this motion in highly non-classical states such as multiphonon Fock states in an electromechanical system⁴⁷, and coupling propagating phonons to qubits^{48–50}. In this context, quantum acoustics has found applications in phonon creation and detection schemes^{51–53}. For a recent review of the prospects of qubit–mechanical coupled systems we refer the reader to ref. 27.

Entanglement and non-classical correlations. One of the hallmarks of quantum physics is the notion of correlations stronger than allowed by classical mechanics, most famously quantum entanglement¹⁶. In quantum mechanics, if two systems are entangled, their individual states before a measurement cannot in principle be described independently; they have to be treated as a single system, no matter how different or far apart they are from one another. A measurement on one seems to directly and instantaneously influence the quantum state of the other. Demonstrating these quantum correlations was a long-sought-after experimental challenge in optomechanics, with the aim of unequivocally demonstrating the existence of a mechanical system in a non-classical state of motion.

The experimental demonstration of an entangled state was accomplished in an electromechanical system where the mechanical motion of a superconducting drum was entangled with a travelling microwave field⁵⁴. In the optical regime, the realization of non-classical correlations between the light field and mechanics was performed using a gigahertz photonic- and phononic-crystal cavity⁵⁵. More recently, continuous-variable entanglement generation of microwave radiation using a mechanical resonator was also demonstrated⁹.

The next conceptual step after creating non-classical correlations between light and mechanics is quantum correlations between two mechanical systems. A photonic- and phononic-crystal cavity was also used to perform phonon counting⁵⁶ or to demonstrate the well known Hanbury Brown–Twiss correlations between phonons⁵⁷ (Fig. 2a–c). The closer the mechanical resonator is to its ground state, the stronger is the effect of quantum correlations; this is seen in Fig. 2c, where the correlation function $g^{(2)}(0)$ dips below 1, which is forbidden for classical excitations, when the initial temperature is sufficiently low. The violation of a Bell inequality is seen as the

ultimate test of non-classicality, as it allows probing of non-classical correlations independently of the validity of quantum physics and—under suitable conditions—in a device-independent manner. For an entangled optomechanical state, a Bell violation was also shown using high-frequency photonic- and phononic-crystal cavities⁵⁸ (Fig. 2d). Creating a non-classical state shared between two mechanical oscillators that are physically separated from one another was also experimentally realized optically using phononic-crystal cavities⁵⁹ and simultaneously in the microwave regime with two superconducting drum resonators^{60–62} (Fig. 3a,b). By calculating an entanglement witness, such as the Simon–Duan criterion¹⁶ that is illustrated in Fig. 3d, one can verify the presence of entanglement between mechanical resonators. It is worth mentioning in this context that entanglement has also been observed between mechanical and spin systems separated by a distance of 1 m (ref. 63).

Most of these experiments were aimed at showing the general feasibility of creating non-classical correlations in an optomechanical system. However, rapid improvements, such as directly reading out states of mechanical motion⁶², should allow the use of entanglement as a starting point for new fundamental experiments and as a resource for novel quantum technologies, including quantum repeaters⁶⁴, and sensors^{65,66}.

An optomechanical toolbox

We now turn our attention to some key applications in emerging quantum technologies of mechanical systems. We will discuss the processing of signals, where marked progress has been made recently in the coherent interconversion between optical and microwave frequencies, and in the optomechanical sensing of displacement. We also focus on how stochastic and quantum thermodynamics, which has also seen an explosion of interest in recent years⁶⁷, can be explored by using optomechanical systems either as heat engines or as probes of thermodynamic quantities or processes, and finish off by reviewing recent progress in designing topologically protected optical or mechanical signal processing devices.


Transduction and signal processing. A key area where mechanical devices have shown unique promise is signal transduction in contexts where disparate resources are to be connected^{18,68,69}, or in cases where the properties of phonons have advantages over photons^{70–72}. This is particularly apparent in electrical quantum systems²⁷ that can be connected to optical photons by means of optomechanical devices. For emerging quantum technologies there is a pressing need for devices that can efficiently and noiselessly convert signals from microwave to optical frequencies: for example, to interface computational devices based on superconducting qubits

Fig. 1 | Platforms for studying optomechanical science. Top left: the optomechanical interaction and a range of couplings enabled by mechanical, electrical and optical functionality. Optomechanical devices can interact with qubits, atoms or other systems: for instance, by means of coupling to strain variations, in the case of defects embedded in mechanical resonators. Optomechanical systems can be used for measuring weak forces (for example, gravity), faint signals (electric or magnetic fields) or small masses. Nonlinear resources can be introduced in optomechanical systems through single-photon counting. **a**, In the prototypical model, an optical cavity is coupled to a mechanical resonator through its displacement x . The physical mechanism underlying this interaction is the change in the resonance frequency of the cavity induced by a displacement of the resonator. We denote the mechanical and optical loss rates by γ and κ , respectively. **b**, Density of states of the mechanical and optical resonances, with resonance frequencies ω_m and ω_c , respectively, and driven by a coherent tone whose frequency is ω_d ; in this illustration we show the red-detuned regime, where the detuning is negative, $\Delta = \omega_d - \omega_c < 0$. Optomechanical phenomena, such as sideband cooling¹⁴⁵, can often be understood physically by considering the relative locations of the driving fields and the peaks in the density of states. **c**, A phononic- and photonic-crystal cavity⁵ with a mechanical resonator in the centre suspended from a phononic shield that assists in minimizing the effects of the environment. **d**, A dielectric nanosphere³⁴, shown in the inset, that can be optically levitated and cooled in an optical cavity. **e**, A mechanical resonator⁹ (lower left and right insets) coupled to a gigahertz microwave circuit (upper left). **f**, A vibrating membrane¹⁴⁶, shown in the inset, coupled dispersively to a high-finesse Fabry–Pérot cavity of fixed length L . **g**, Brillouin optomechanics, which exploits bulk crystal vibrations³⁹. **h**, Optomechanical physics in superfluid helium³⁷ with an optical cavity bounded by two optical fibres and a mechanical resonator formed from an acoustic mode in the helium. **i**, An optomechanical membrane incorporating a phononic crystal that possesses very long mechanical coherence times¹⁴²; a membrane of this kind could be used inside a cavity much like the one in **f**. **j**, A pair of parallel-plate capacitors in an LC resonator whose capacitance is modified by the vibrational motion of their plates. Panels adapted with permission from: **c**, ref. 5, Springer Nature Ltd; **d**, ref. 34, AAAS; **e**, ref. 9, Springer Nature Ltd.; **f**, ref. 146, Springer Nature Ltd.; **g**, ref. 39, Springer Nature Ltd.; **h**, ref. 37, APS; **i**, ref. 142, Springer Nature Ltd.; **j**, ref. 62, AAAS.

with telecommunications networks. Mechanical motion has been shown to couple well to both optical and electrical signals simultaneously. Despite a plethora of other potential technologies, including direct electro-optic conversion in nonlinear crystals such as lithium niobate^{73–77}, mechanical systems are thus far the only platform to have experimentally demonstrated the most important characteristics required of such a transduction device, including conversion that approaches unit efficiency⁷⁸, low-noise operation⁷⁹

and conversion of single-photon-level signals by coupling to a superconducting qubit⁸⁰.

Figure 4 illustrates different concepts for transduction and phase-coherent conversion between microwave signals from a superconducting qubit to optical light. Gigahertz-frequency piezoelectric devices can be used to couple directly to both qubits and light through a photonic-crystal cavity. In these experiments, Fig. 4a–c, a mechanical object such as a thin membrane is






Fig. 2 | Non-classical correlations in and between mechanical resonators. **a**, A scanning electron microscope image of an optomechanical device⁵⁷ used to generate correlations between phonons. **b**, The experimental protocol employed consists of optically exciting a mechanical resonator with a single phonon and reading it back out after a time delay $\Delta\tau$. **c**, The zero-time second-order correlation function $g^{(2)}(0)$; values below 1 denote non-classical Hanbury Brown-Twiss correlations between phonons⁵⁷. **d**, Experimental protocol used to demonstrate a violation of a Bell inequality in an optomechanical system with two mechanical resonators⁵⁸; the state is initialized at $t=0$ and read out optically after a time delay $t=\Delta\tau$, with entanglement between the mechanical resonators converted to correlations between photons. Each branch consists of a device similar to that in **a**. Panels adapted with permission from: **a,c**, ref. 57, AAAS; **d**, ref. 58, APS.

simultaneously coupled to an optical and to a microwave cavity, as shown schematically in Fig. 4b, resulting in the standard optomechanical interaction linearized by a strong pump. This kind of double parametric coupling has the advantage of not requiring frequency matching or piezoelectric materials. Well understood




Fig. 3 | Entanglement of massive mechanical resonators. **a,b**, Schematic of the experiment, consisting of two mechanical resonators coupled to a single electromagnetic cavity, in this case an LC resonator that is coupled inductively to an input and output port (**a**), and a micrograph of the device used to conduct an experiment in which a superconducting microwave resonator is coupled to two mechanical drum-head resonators (**b**). **c**, Entanglement between two mechanical resonators is best understood in terms of uncertainties. When the resonators are in an entangled state, the uncertainties in two collective coordinates (Δx_{\pm} , the uncertainty in the difference of the positions, and Δp_{\pm} , the uncertainty in the sum of the momenta) go below the size of the zero-point fluctuations (Δx_{zpt} , Δp_{zpt}). **d**, The Simon-Duan criterion $(\Delta x_{\pm}/\Delta x_{zpt} + \Delta p_{\pm}/\Delta p_{zpt})/2$, which is a witness for the presence of entanglement when its value dips below unity; the horizontal axis corresponds to the angle of the collective mechanical quadrature along which the entanglement was produced, demonstrating the ability to generate entanglement along any chosen collective quadrature. The solid red horizontal line is the theoretical prediction. Panels adapted with permission from: **b**, ref. 62, AAAS; **c**, ref. 60, Springer Nature Ltd.; **d**, ref. 61, AAAS.

signatures of coherent conversion, visible interferometric fringes and Rabi oscillations, have been observed and are shown in Fig. 4d–f. Early experiments showed that microwave driving of this kind of system can yield an optical signal⁸¹, and recent developments of this concept have observed optical photons transduced from a superconducting qubit^{79,80}. Nanoscale devices, however, currently have efficiencies far from what is




Fig. 4 | Efficient and coherent transduction in optomechanical systems.

a, Principle of operation of an optomechanical transducer⁸². **b**, Schematic of an optomechanical transducer coupled to a microwave resonator, forming a microwave-to-optical photon converter. **c**, The efficiency of this converter; its maximum efficiency was measured to be approximately 47% (ref. ⁸²), obtained by setting the mechanical damping rate appropriately. **d**, Coherent conversion between optics and microwaves using a mechanical transducer⁷⁹; interference of the original microwave signal with a phase-delayed signal converted to light and back is evidence of phase-coherent transduction between optical and microwave radiation. **e**, Principle of operation of an optomechanical transducer that is used to couple a qubit to an optical fibre⁸⁰; Ω is the excitation rate applied when exciting the qubit between its two states. **f**, Quantum-coherent interconversion between microwave photons and phonons in an electromechanical circuit⁸⁰. In this experiment, Rabi oscillations shift excitations coherently between the qubit and the mechanical resonator; this is evidenced by the oscillating qubit population. Inset: the level structure for the coupled qubit (levels g and e , and qubit frequency ν_0) and mechanical oscillator (number states 0 and 1, and mechanical frequency ν_m). Panels adapted with permission from: **a, e, f**, ref. ⁸⁰, Springer Nature Ltd.; **c**, ref. ⁸², Springer Nature Ltd.; **d**, ref. ⁷⁹, Springer Nature Ltd.

needed for heterogeneous quantum networks. Approaches using low-frequency mechanical resonators have achieved much higher conversion efficiencies, close to 50% (refs. ^{78,82,83}), yet still with some added noise that must be removed for quantum operation.

Displacement sensing with optomechanics. Optomechanics is also inextricably linked to precise interferometric measurement of mechanical motion. In fact, early thinking on optical radiation pressure effects in mechanical devices stemmed from explorations into fundamental limits of precision sensors^{13,84}. Small-scale optomechanical devices have played a role in understanding application of quantum sensing concepts to detecting mechanical motion. Shot noise places a limit on the imprecision of any interferometer, and, while the ratio of signal to noise can be improved by increasing probe strength, eventually quantum backaction in the form of the shot noise of radiation pressure will obscure the measurement. The balance of these two sources in a typical interferometer configuration is often referred to as the standard quantum limit. Seminal works put forth the idea of backaction-evading measurements⁸⁵, which have been applied for example in microwave cavity-based devices^{86,87}. An active area of research is constructing quantum-mechanics-free subspaces, where all variables are quantum non-demolition observables^{61,63,88}.

Squeezing of the quantum noise of light is a key opportunity for improving mechanical detectors. The use of squeezed light to reduce imprecision due to shot noise has been demonstrated in pioneering experiments and recently even in the LIGO gravitational-wave observatories^{89,90}. The use of squeezed resources becomes even more effective when radiation pressure shot noise plays a role in the observed quantum limits^{91,92}. In the regime where radiation pressure shot noise is a dominant effect on the motion of mechanical devices, as is natural in optomechanical devices, so-called ponderomotive squeezing of light can be obtained by harnessing the entangling interaction that occurs with blue-detuned light in cavity optomechanics (Box 1)^{93–96}. This illustrates an interesting feature of optomechanics: namely, while light can be used to manipulate mechanical motion in the quantum regime, mechanical motion, even as a classical object, can also manipulate the quantum properties of light. Ponderomotive squeezing can be harnessed to improve displacement detection⁹⁷, a concept that has been shown experimentally near the standard quantum limit of an interferometer and beyond^{98,99}, and has now even been observed in the kilogram-scale mirrors of LIGO¹⁰⁰. The quantum sensing frontier is ever expanding in gravitational-wave detectors, and a next goal is the injection of frequency-dependent squeezing to achieve broadband gains in sensitivity^{101,102}.

Thermodynamics and thermal machines. The prototypical optomechanical setting, Fig. 1a, bears a strong resemblance to the paradigm of a thermodynamic system, namely a chamber filled with a gas and endowed with a movable piston. This analogy has been recently pushed all the way to the proposal and implementation of prototype heat engines based on optomechanical dynamics with the ambition to explore finite-time thermodynamics in both classical and quantum contexts.

In practice, the Hamiltonian (3) is complemented by the interaction of the mechanical motion and the electromagnetic field with their respective environments, which can be at different temperatures. The optomechanical coupling between the cavity field and mechanical motion results in hybrid photon–phonon excitations that can be tuned from phonon-like to photon-like by varying the driving laser frequency. In turn, this implies that the corresponding excitations are coupled to either the phononic or the photonic environments, respectively. The different effective temperatures of these two thermal reservoirs have been exploited to arrange an Otto cycle^{103–105}. Feedback-based mechanisms can be put in place




Fig. 5 | Non-reciprocal effects in optomechanical systems. **a**, Concept underlying non-reciprocal transport in an optomechanical network.¹¹⁷ Excitations can travel between modes \hat{a}_1 and \hat{a}_2 via the upper or lower pathways, involving mode \hat{b}_1 or \hat{b}_2 , respectively; appropriately choosing the phase difference ϕ between the two allows for transport in one direction to be suppressed with respect to the other. **b**, A topological nanoelectromechanical metamaterial composed of a patterned SiN nanomembrane suspended over a doped silicon substrate¹²⁵. Inset: the hexagonal unit cell. **c**, Demonstration of a reconfigurable non-reciprocal optomechanical device¹¹⁷, showing the scattering parameters between two ports of the device; from left to right, the circuit is set up to allow transmission only from port 1 to port 2, in either direction, and only from port 2 to port 1. **d**, An experimental demonstration of a mechanical on-chip microwave circulator⁴⁵ set up to transmit signals from any port to the next one in an anticlockwise direction, but not in reverse; the figure shows the transmission between pairs of ports on the device. **e**, Frequency dispersion curves of the topological optomechanical structure shown in **b**¹²⁵, which supports topologically protected chiral transport; the experimental measurements (left) mirror the theoretical calculations (right) closely. Panels adapted with permission from: **a,c**, ref. ¹¹⁷, Springer Nature Ltd.; **d**, ref. ⁴⁵, Springer Nature Ltd.; **b,e**, ref. ¹²⁵, Springer Nature Ltd.

to bypass the necessity of strong optomechanical coupling¹⁰⁶ that would otherwise be required to hybridize the photonic and phononic excitations. While in this scheme a thermodynamic cycle is

induced by modulating a laser frequency, alternative approaches to continuous work extraction make use of a temperature gradient between the thermal baths, between which the engine operates to sustain mechanical oscillations¹⁰⁷ in an autonomous manner, or a broadband heat bath with no coherence or phase-locking¹⁰⁸. A particularly interesting platform for work extraction is the levitated optomechanical scenario consisting of a submicrometre particle optically trapped in a harmonic potential with controllable mechanical frequency¹⁰⁹ (Fig. 1d). The thermal environment embodied by the residual gas in the trap provides the heat bath for this system. A Stirling engine can then be operated by weakly coupling the underdamped mechanical motion to the optical cavity.

The potential of optomechanical systems for sensing and probing extends to the assessment of crucial quantities in finite-time non-equilibrium thermodynamics. Specifically, it offers the possibility to study the interplay between interaction and incoherent dynamics induced by the coupling with environments. This interplay enables the preparation of non-equilibrium steady states and the study of the entropy production process resulting from their deviation from thermal equilibrium¹¹⁰. In optomechanical systems, entropy production—which in essence is a non-equilibrium formulation of the second principle of thermodynamics¹¹⁰—can be experimentally characterized by accessing the steady-state noise spectral density¹¹¹. This quantity provides key information on the entropy fluxes from the optical and mechanical subsystems to the respective thermal environment. This idea has been extended to address the entropic term resulting from the continuous measurement to which the optomechanical system is exposed, thus demonstrating the substantial contribution arising from the information gathered through measurement¹¹². The entropy production resulting from the relaxation of the non-equilibrium initial state of motion of a mechanical system, and the characterization of the environment into which the system is embedded¹¹³, have been at the focus of recent experimental endeavours.

Non-reciprocal transport of photons and phonons. A final field of study that we choose to highlight as promising for quantum applications is that of non-reciprocal transport, one key technological application of which is in chip-scale circulators for electromagnetic radiation. In traditional large-scale optics, circulators rely on strong permanent magnets to break time-reversal symmetry. Around a decade ago it was realized that the optomechanical interaction can be exploited in place of a magnetic field^{114–116}. This opened the door to the realization of non-reciprocal optomechanical devices^{45,117–122}, whose operation we illustrate in Fig. 5a,b. These devices have been used to demonstrate capabilities unique to optomechanical devices, most notably the potential for full reconfigurability^{45,117} in the sense of in situ selection of the direction of signal propagation through the device; this is demonstrated clearly in Fig. 5c,d by observing the transmission of electromagnetic radiation between pairs of inputs and outputs.

Optomechanical platforms are uniquely suited to creating pseudomagnetic fields¹²³ and topological insulators¹²⁴ for light and sound. These ideas have started becoming an experimental reality only recently; one recent demonstration of topologically protected transport in an optomechanical system^{125,126} is shown in Fig. 5e. Non-reciprocal physics has been proposed or observed in periodic optomechanical structures, including one- and two-dimensional phononic or photonic crystals^{127–129}, arrays of mechanical resonators interacting with a single optical mode¹³⁰ and other optical or mechanical platforms^{131–133}.

Observations, outlook and outstanding challenges

The interaction of electromagnetic radiation with the motion of objects has an array of implications and manifestations. The field has grown rapidly since the proof-of-principle experiments that

demonstrated the use of light to dampen the motion of relatively large mechanical oscillators⁴. The quests to reach the quantum ground state of a mechanical oscillator, to put one in a non-classical state of motion and to entangle two mechanical oscillators have all been completed. It is now time to look ahead at how optomechanical devices may be applied in forthcoming quantum technologies and as the basis for new experiments.

Looking beyond the accomplishments that we have reviewed paints an interesting picture. Fundamental exploration has always played a large role in the development of the field of optomechanics. In this spirit, we describe some interesting directions, which we believe could have scientific and, eventually, technological implications: optomechanical systems present the prospect of pushing quantum experiments to ever larger mass scales; the theoretical underpinnings of where new physics might lie—collapse models¹³⁴, a resolution of the measurement problem¹³⁵, gravitational decoherence¹³⁶, to name but a few—is an open question that optomechanics is uniquely suited to explore. The dynamical Casimir effect^{137,138}, which describes the production of photons from the vacuum due to rapidly moving boundaries, also lends itself to optomechanical realization; recent studies encouragingly suggest the possibility of bypassing the constraint for its observation set by the demand of high mechanical frequencies¹³⁹. Finally, other interesting frontiers rely upon the unique coherence and the length scale of mechanical excitations in optomechanical devices; active areas of investigation include using long-lived coherent phononic memories^{140–142} for quantum repeaters and interconnecting quantum processors using phononic excitations and waveguides^{72,143,144}.

We expect that the research landscape will increasingly focus on refining the applications of optomechanical devices in quantum technologies, on the one hand, and on understanding fundamental phenomena such as those above, on the other. Cross-fertilization between these two branches will probably remain a hallmark of the field, bringing new insight and advances to materials science, nano- and microstructure fabrication, and fundamental quantum science, to investigate among other topics the emergence of new physics.

Received: 23 February 2021; Accepted: 1 October 2021;
Published online: 6 December 2021

References

- Ashkin, A. The pressure of laser light. *Sci. Am.* **226**, 62–71 (1972).
- Einstein, A. Zur Quantentheorie der Strahlung. *Phys. Z.* **18**, 121–128 (1917).
- Kepler, J. *De Cometis Libelli Tres I. Astronomicus, Theoremata Continens de Novam... III. Astrologicus, de Significationibus Cometarum Annorum Motu Cometarum... II. Physicus, Continens Physiologiam Cometarum 1607 et 1618* (Mylly, 1619).
- Aspelmeyer, M., Kippenberg, T. J. & Marquardt, F. Cavity optomechanics. *Rev. Mod. Phys.* **86**, 1391–1452 (2014).
- Chan, J. et al. Laser cooling of a nanomechanical oscillator into its quantum ground state. *Nature* **478**, 89–92 (2011).
- Verhagen, E., Deléglise, S., Weis, S., Schliesser, A. & Kippenberg, T. J. Quantum-coherent coupling of a mechanical oscillator to an optical cavity mode. *Nature* **482**, 63–67 (2012).
- Wollman, E. E. et al. Quantum squeezing of motion in a mechanical resonator. *Science* **349**, 952–955 (2015).
- Pirkkalainen, J. M., Damskäg, E., Brandt, M., Massel, F. & Sillanpää, M. A. Squeezing of quantum noise of motion in a micromechanical resonator. *Phys. Rev. Lett.* **115**, 243601 (2015).
- Barzanjeh, S. et al. Stationary entangled radiation from micromechanical motion. *Nature* **570**, 480–483 (2019).
- Dowling, J. P. & Milburn, G. J. Quantum technology: the second quantum revolution. *Philos. Trans. R. Soc. A* **361**, 1655–1674 (2003).
- Rogers, B., Lo Gullo, N., De Chiara, G., Palma, G. M. & Paternostro, M. Hybrid optomechanics for quantum technologies. *Quantum Meas. Quantum Metrol.* **2**, 11–43 (2014).
- Kurizki, G. et al. Quantum technologies with hybrid systems. *Proc. Natl Acad. Sci. USA* **112**, 3866–3873 (2015).
- Braginskii, V. B. & Manukin, A. B. *Measurement of Weak Forces in Physics Experiments* (Univ. Chicago Press, 1977).
- Clerk, A. A., Devoret, M. H., Girvin, S. M., Marquardt, F. & Schoelkopf, R. J. Introduction to quantum noise, measurement, and amplification. *Rev. Mod. Phys.* **82**, 1155–1208 (2010).
- Hanbury Brown, R. & Twiss, R. Q. Correlation between photons in two coherent beams of light. *Nature* **177**, 27–29 (1956).
- Horodecki, R., Horodecki, P., Horodecki, M. & Horodecki, K. Quantum entanglement. *Rev. Mod. Phys.* **81**, 865–942 (2009).
- Brunner, N., Cavalcanti, D., Pironio, S., Scarani, V. & Wehner, S. Bell nonlocality. *Rev. Mod. Phys.* **86**, 419–478 (2014).
- Lauk, N. et al. Perspectives on quantum transduction. *Quantum Sci. Technol.* **5**, 020501 (2020).
- Lambert, N. J., Rueda, A., Sedlmeir, F. & Schwefel, H. G. L. Coherent conversion between microwave and optical photons—an overview of physical implementations. *Adv. Quantum Technol.* **3**, 1900077 (2020).
- Gemmer, J., Michel, M. & Mahler, G. *Quantum Thermodynamics* Vol. 784 (Springer, 2009).
- Vinjanampathy, S. & Anders, J. Quantum thermodynamics. *Contemp. Phys.* **57**, 545–579 (2016).
- Bohr Brask, J., Haack, G., Brunner, N. & Huber, M. Autonomous quantum thermal machine for generating steady-state entanglement. *New J. Phys.* **17**, 113029 (2015).
- Karrai, K., Favero, I. & Metzger, C. Doppler optomechanics of a photonic crystal. *Phys. Rev. Lett.* **100**, 240801 (2008).
- Xuerb, A., Domokos, P., Asbóth, J., Horak, P. & Fregard, T. Scattering theory of cooling and heating in optomechanical systems. *Phys. Rev. A* **79**, 053810 (2009).
- O’Connell, A. D. et al. Quantum ground state and single-phonon control of a mechanical resonator. *Nature* **464**, 697–703 (2010).
- Chu, Y. et al. Quantum acoustics with superconducting qubits. *Science* **358**, 199–202 (2017).
- Clerk, A. A., Lehnert, K. W., Bertet, P., Petta, J. R. & Nakamura, Y. Hybrid quantum systems with circuit quantum electrodynamics. *Nat. Phys.* **16**, 257–267 (2020).
- Teufel, J. D. et al. Sideband cooling of micromechanical motion to the quantum ground state. *Nature* **475**, 359–363 (2011).
- Peterson, R. W. et al. Laser cooling of a micromechanical membrane to the quantum backaction limit. *Phys. Rev. Lett.* **116**, 063601 (2016).
- Rossi, M., Mason, D., Chen, J., Tsaturyan, Y. & Schliesser, A. Measurement-based quantum control of mechanical motion. *Nature* **563**, 53–58 (2018).
- Clark, J. B., Lecocq, F., Simmonds, R. W., Aumentado, J. & Teufel, J. D. Sideband cooling beyond the quantum backaction limit with squeezed light. *Nature* **541**, 191–195 (2017).
- Safavi-Naeini, A. H. et al. Observation of quantum motion of a nanomechanical resonator. *Phys. Rev. Lett.* **108**, 033602 (2012).
- Millen, J. & Stickler, B. A. Quantum experiments with microscale particles. *Contemp. Phys.* **61**, 155–168 (2020).
- Delić, U. et al. Cooling of a levitated nanoparticle to the motional quantum ground state. *Science* **367**, 892–895 (2020).
- Magrini, L. et al. Real-time optimal quantum control of mechanical motion at room temperature. *Nature* **595**, 373–377 (2021).
- Tebbenjohanns, F., Mattana, M. L., Rossi, M., Frimmer, M. & Novotny, L. Quantum control of a nanoparticle optically levitated in cryogenic free space. *Nature* **595**, 378–382 (2021).
- Shkarin, A. B. et al. Quantum optomechanics in a liquid. *Phys. Rev. Lett.* **122**, 153601 (2019).
- He, X. et al. Strong optical coupling through superfluid Brillouin lasing. *Nat. Phys.* **16**, 417–421 (2020).
- Renninger, W. H., Kharel, P., Behunin, R. O. & Rakich, P. T. Bulk crystalline optomechanics. *Nat. Phys.* **14**, 601–607 (2018).
- Ferraro, A., Olivares, S. & Paris, M. *Gaussian States in Quantum Information* (Napoli Series on Physics and Astrophysics, Bibliopolis, 2005).
- Reed, A. P. et al. Faithful conversion of propagating quantum information to mechanical motion. *Nat. Phys.* **13**, 1163–1167 (2017).
- Clerk, A. A. in *Quantum Optomechanics and Nanomechanics* (eds Cohadon, P.-F. et al.) 183–236 (Oxford Univ. Press, 2020).
- Vogel, W., Welsch, D.-G. & Wallentowitz, S. *Quantum Optics: an Introduction* (Wiley-VCH, 2005).
- Lecocq, F., Clark, J. B., Simmonds, R. W., Aumentado, J. & Teufel, J. D. Quantum nondemolition measurement of a nonclassical state of a massive object. *Phys. Rev. X* **5**, 041037 (2015).
- Barzanjeh, S. et al. Mechanical on-chip microwave circulator. *Nat. Commun.* **8**, 953 (2017).
- Delaney, R. D., Reed, A. P., Andrews, R. W. & Lehnert, K. W. Measurement of motion beyond the quantum limit by transient amplification. *Phys. Rev. Lett.* **123**, 183603 (2019).
- Chu, Y. et al. Creation and control of multiphonon Fock states in a bulk acoustic-wave resonator. *Nature* **563**, 666–670 (2018).

48. Manenti, R. et al. Circuit quantum acoustodynamics with surface acoustic waves. *Nat. Commun.* **8**, 975 (2017).
49. Moores, B. A., Sletten, L. R., Viennot, J. J. & Lehnert, K. W. Cavity quantum acoustic device in the multimode strong coupling regime. *Phys. Rev. Lett.* **120**, 227701 (2018).
50. Bienfait, A. et al. Quantum erasure using entangled surface acoustic phonons. *Phys. Rev. X* **10**, 021055 (2020).
51. Viennot, J. J., Ma, X. & Lehnert, K. W. Phonon-number-sensitive electromechanics. *Phys. Rev. Lett.* **121**, 183601 (2018).
52. Arrangoiz-Arriola, P. et al. Resolving the energy levels of a nanomechanical oscillator. *Nature* **571**, 537–540 (2019).
53. Sletten, L. R., Moores, B. A., Viennot, J. J. & Lehnert, K. W. Resolving phonon Fock states in a multimode cavity with a double-slit qubit. *Phys. Rev. X* **9**, 021056 (2019).
54. Palomaki, T. A., Teufel, J. D., Simmonds, R. W. & Lehnert, K. W. Entangling mechanical motion with microwave fields. *Science* **342**, 710–713 (2013).
55. Riedinger, R. et al. Non-classical correlations between single photons and phonons from a mechanical oscillator. *Nature* **530**, 313–316 (2016).
56. Cohen, J. D. et al. Phonon counting and intensity interferometry of a nanomechanical resonator. *Nature* **520**, 522–525 (2015).
57. Hong, S. et al. Hanbury Brown and Twiss interferometry of single phonons from an optomechanical resonator. *Science* **358**, 203–206 (2017).
58. Marinković, I. et al. Optomechanical Bell test. *Phys. Rev. Lett.* **121**, 220404 (2018).
59. Riedinger, R. et al. Remote quantum entanglement between two micromechanical oscillators. *Nature* **556**, 473–477 (2018).
60. Ockeloen-Korppi, C. F. et al. Stabilized entanglement of massive mechanical oscillators. *Nature* **556**, 478–482 (2018).
61. Mercier de Lépinay, L., Ockeloen-Korppi, C. F., Woolley, M. J. & Sillanpää, M. A. Quantum mechanics-free subsystem with mechanical oscillators. *Science* **372**, 625–629 (2021).
62. Kotler, S. et al. Direct observation of deterministic macroscopic entanglement. *Science* **372**, 622–625 (2021).
63. Thomas, R. A. et al. Entanglement between distant macroscopic mechanical and spin systems. *Nat. Phys.* **17**, 228–233 (2021).
64. Fiaschi, N. et al. Optomechanical quantum teleportation. *Nat. Photon.* **15**, 817–821 (2021).
65. Barzanjeh, S. et al. Microwave quantum illumination. *Phys. Rev. Lett.* **114**, 080503 (2015).
66. Barzanjeh, S., Pirandola, S., Vitali, D. & Fink, J. M. Microwave quantum illumination using a digital receiver. *Sci. Adv.* **6**, eabb0451 (2020).
67. Defner, S. & Campbell, S. *Quantum Thermodynamics: an Introduction to the Thermodynamics of Quantum Information* (Morgan & Claypool, 2019).
68. Tian, L. & Wang, H. Optical wavelength conversion of quantum states with optomechanics. *Phys. Rev. A* **82**, 053806 (2010).
69. Barzanjeh, S., Abdi, M., Milburn, G. J., Tombesi, P. & Vitali, D. Reversible optical-to-microwave quantum interface. *Phys. Rev. Lett.* **109**, 130503 (2012).
70. Habraken, S. J. M., Stannigel, K., Lukin, M. D., Zoller, P. & Rabl, P. Continuous mode cooling and phonon routers for phononic quantum networks. *New J. Phys.* **14**, 115004 (2012).
71. Vermersch, B., Guimond, P. O., Pichler, H. & Zoller, P. Quantum state transfer via noisy photonic and phononic waveguides. *Phys. Rev. Lett.* **118**, 133601 (2017).
72. Patel, R. N. et al. Single-mode phononic wire. *Phys. Rev. Lett.* **121**, 040501 (2018).
73. Rueda, A. et al. Efficient microwave to optical photon conversion: an electro-optical realization. *Optica* **3**, 597–604 (2016).
74. Rueda, A., Hease, W., Barzanjeh, S. & Fink, J. M. Electro-optic entanglement source for microwave to telecom quantum state transfer. *npj Quantum Inf.* **5**, 108 (2019).
75. McKenna, T. P. et al. Cryogenic microwave-to-optical conversion using a triply resonant lithium-niobate-on-sapphire transducer. *Optica* **7**, 1737–1745 (2020).
76. Hease, W. et al. Bidirectional electro-optic wavelength conversion in the quantum ground state. *PRX Quantum* **1**, 020315 (2020).
77. Han, X. et al. Cavity piezo-mechanics for superconducting–nanophotonic quantum interface. *Nat. Commun.* **11**, 3237 (2020).
78. Andrews, R. W. et al. Bidirectional and efficient conversion between microwave and optical light. *Nat. Phys.* **10**, 321–326 (2014).
79. Fersch, M. et al. Microwave-to-optics conversion using a mechanical oscillator in its quantum ground state. *Nat. Phys.* **16**, 69–74 (2019).
80. Mirhosseini, M., Sipahigil, A., Kalaei, M. & Painter, O. Superconducting qubit to optical photon transduction. *Nature* **588**, 599–603 (2020).
81. Bochmann, J., Vainsencher, A., Awschalom, D. D. & Cleland, A. N. Nanomechanical coupling between microwave and optical photons. *Nat. Phys.* **9**, 712–716 (2013).
82. Higginbotham, A. P. et al. Harnessing electro-optic correlations in an efficient mechanical converter. *Nat. Phys.* **14**, 1038–1042 (2018).
83. Arnold, G. et al. Converting microwave and telecom photons with a silicon photonic nanomechanical interface. *Nat. Commun.* **11**, 4460 (2020).
84. Caves, C. M., Thorne, K. S., Drever, R. W., Sandberg, V. D. & Zimmermann, M. On the measurement of a weak classical force coupled to a quantum-mechanical oscillator. I. Issues of principle. *Rev. Mod. Phys.* **52**, 341 (1980).
85. Braginsky, V. B., Vorontsov, Y. I. & Thorne, K. S. Quantum nondemolition measurements. *Science* **209**, 547–557 (1980).
86. Hertzberg, J. et al. Back-action-evading measurements of nanomechanical motion. *Nat. Phys.* **6**, 213–217 (2010).
87. Ockeloen-Korppi, C. et al. Quantum backaction evading measurement of collective mechanical modes. *Phys. Rev. Lett.* **117**, 140401 (2016).
88. Tsang, M. & Caves, C. M. Evading quantum mechanics: engineering a classical subsystem within a quantum environment. *Phys. Rev. X* **2**, 031016 (2012).
89. Aasi, J. et al. Enhanced sensitivity of the LIGO gravitational wave detector by using squeezed states of light. *Nat. Photon.* **7**, 613–619 (2013).
90. Tse, M. E. et al. Quantum-enhanced advanced LIGO detectors in the era of gravitational-wave astronomy. *Phys. Rev. Lett.* **123**, 231107 (2019).
91. Purdy, T. P., Peterson, R. W. & Regal, C. A. Observation of radiation pressure shot noise on a macroscopic object. *Science* **339**, 801–804 (2013).
92. Cripe, J. et al. Measurement of quantum back action in the audio band at room temperature. *Nature* **568**, 364–367 (2019).
93. Brooks, D. W. et al. Non-classical light generated by quantum-noise-driven cavity optomechanics. *Nature* **488**, 476–480 (2012).
94. Safavi-Naeini, A. H. et al. Squeezed light from a silicon micromechanical resonator. *Nature* **500**, 185–189 (2013).
95. Purdy, T. P., Yu, P. L., Peterson, R. W., Kampel, N. S. & Regal, C. A. Strong optomechanical squeezing of light. *Phys. Rev. X* **3**, 031012 (2013).
96. Clark, J. B., Lecocq, F., Simmonds, R. W., Aumentado, J. & Teufel, J. D. Observation of strong radiation pressure forces from squeezed light on a mechanical oscillator. *Nat. Phys.* **12**, 683–687 (2016).
97. Vyatchanin, S. & Zubova, E. Quantum variation measurement of a force. *Phys. Lett. A* **201**, 269–274 (1995).
98. Kampel, N. S. et al. Improving broadband displacement detection with quantum correlations. *Phys. Rev. X* **7**, 021008 (2017).
99. Mason, D., Chen, J., Rossi, M., Tsaturyan, Y. & Schliesser, A. Continuous force and displacement measurement below the standard quantum limit. *Nat. Phys.* **15**, 745–749 (2019).
100. Li, Y. L. & Barker, P. F. Characterization and testing of a micro-g whispering gallery mode optomechanical accelerometer. *J. Lightwave Technol.* **36**, 3919–3926 (2018).
101. Yap, M. J. et al. Broadband reduction of quantum radiation pressure noise via squeezed light injection. *Nat. Photon.* **14**, 19–23 (2020).
102. McCuller, L. et al. Frequency-dependent squeezing for advanced LIGO. *Phys. Rev. Lett.* **124**, 171102 (2020).
103. Zhang, K., Bariani, F. & Meystre, P. Quantum optomechanical heat engine. *Phys. Rev. Lett.* **112**, 150602 (2014).
104. Zhang, K., Bariani, F. & Meystre, P. Theory of an optomechanical quantum heat engine. *Phys. Rev. A* **90**, 023819 (2014).
105. Dong, Y., Zhang, K., Bariani, F. & Meystre, P. Work measurement in an optomechanical quantum heat engine. *Phys. Rev. A* **92**, 033854 (2015).
106. Abari, N. E., Angelis, G. V. D., Zippilli, S. & Vitali, D. An optomechanical heat engine with feedback-controlled in-loop light. *New J. Phys.* **21**, 093051 (2019).
107. Mari, A., Farace, A. & Giovannetti, V. Quantum optomechanical piston engines powered by heat. *J. Phys. B* **48**, 175501 (2015).
108. Gelbwaser-Klimovsky, D. & Kurizki, G. Work extraction from heat-powered quantized optomechanical setups. *Sci. Rep.* **5**, 7809 (2015).
109. Dechant, A., Kiesel, N. & Lutz, E. All-optical nanomechanical heat engine. *Phys. Rev. Lett.* **114**, 183602 (2015).
110. Landi, G. T. & Paternostro, M. Irreversible entropy production, from quantum to classical. *Rev. Mod. Phys.* **93**, 035008 (2021).
111. Brunelli, M. et al. Experimental determination of irreversible entropy production in out-of-equilibrium mesoscopic quantum systems. *Phys. Rev. Lett.* **121**, 160604 (2018).
112. Belenchia, A., Mancino, L., Landi, G. T. & Paternostro, M. Entropy production in continuously measured quantum systems. *npj Quant. Inf.* **6**, 97 (2020).
113. Millen, J., Deesuan, T., Barker, P. & Anders, J. Nanoscale temperature measurements using non-equilibrium Brownian dynamics of a levitated nanosphere. *Nat. Nanotechnol.* **9**, 425–429 (2014).
114. Hafezi, M. & Rabl, P. Optomechanically induced non-reciprocity in microring resonators. *Opt. Express* **20**, 7672 (2012).
115. Metelmann, A. & Clerk, A. A. Nonreciprocal photon transmission and amplification via reservoir engineering. *Phys. Rev. X* **5**, 021025 (2015).
116. Miri, M.-A., Ruesink, F., Verhagen, E. & Alù, A. Optical nonreciprocity based on optomechanical coupling. *Phys. Rev. Appl.* **7**, 064014 (2017).

117. Bernier, N. R. et al. Nonreciprocal reconfigurable microwave optomechanical circuit. *Nat. Commun.* **8**, 604 (2017).
118. Barzanjeh, S., Aquilina, M. & Xuereb, A. Manipulating the flow of thermal noise in quantum devices. *Phys. Rev. Lett.* **120**, 060601 (2018).
119. Peterson, G. A. et al. Demonstration of efficient nonreciprocity in a microwave optomechanical circuit. *Phys. Rev. X* **7**, 031001 (2017).
120. Fang, K. et al. Generalized non-reciprocity in an optomechanical circuit via synthetic magnetism and reservoir engineering. *Nat. Phys.* **13**, 465–471 (2017).
121. Ruesink, F., Miri, M.-A., Alù, A. & Verhagen, E. Nonreciprocity and magnetic-free isolation based on optomechanical interactions. *Nat. Commun.* **7**, 13662 (2016).
122. Xu, X.-W. & Li, Y. Optical nonreciprocity and optomechanical circulator in three-mode optomechanical systems. *Phys. Rev. A* **91**, 053854 (2015).
123. Brendel, C., Peano, V., Painter, O. J. & Marquardt, F. Pseudomagnetic fields for sound at the nanoscale. *Proc. Natl Acad. Sci. USA* **114**, E3390–E3395 (2017).
124. Peano, V., Brendel, C., Schmidt, M. & Marquardt, F. Topological phases of sound and light. *Phys. Rev. X* **5**, 031011 (2015).
125. Cha, J., Kim, K. W. & Daraio, C. Experimental realization of on-chip topological nanoelectromechanical metamaterials. *Nature* **564**, 229–233 (2018).
126. Ren, H. et al. Topological phonon transport in an optomechanical system. Preprint at <https://arxiv.org/abs/2009.06174> (2020).
127. Heinrich, G., Ludwig, M., Qian, J., Kubala, B. & Marquardt, F. Collective dynamics in optomechanical arrays. *Phys. Rev. Lett.* **107**, 043603 (2011).
128. Schmidt, M., Peano, V. & Marquardt, F. Optomechanical Dirac physics. *New J. Phys.* **17**, 023025 (2015).
129. Sanavio, C., Peano, V. & Xuereb, A. Nonreciprocal topological phononics in optomechanical arrays. *Phys. Rev. B* **101**, 085108 (2020).
130. Gan, J.-H., Xiong, H., Si, L.-G., Lü, X.-Y. & Wu, Y. Solitons in optomechanical arrays. *Opt. Lett.* **41**, 2676 (2016).
131. Hafezi, M., Mittal, S., Fan, J., Migdall, A. & Taylor, J. M. Imaging topological edge states in silicon photonics. *Nat. Photon.* **7**, 1001–1005 (2013).
132. Mousavi, S. H., Khanikaev, A. B. & Wang, Z. Topologically protected elastic waves in phononic metamaterials. *Nat. Commun.* **6**, 8682 (2015).
133. Brendel, C., Peano, V., Painter, O. & Marquardt, F. Snowflake phononic topological insulator at the nanoscale. *Phys. Rev. B* **97**, 020102 (2018).
134. Bassi, A., Lochan, K., Satin, S., Singh, T. P. & Ulbricht, H. Models of wave-function collapse, underlying theories, and experimental tests. *Rev. Mod. Phys.* **85**, 471–527 (2013).
135. Schlosshauer, M. Decoherence, the measurement problem, and interpretations of quantum mechanics. *Rev. Mod. Phys.* **76**, 1267–1305 (2004).
136. Bassi, A., Großardt, A. & Ulbricht, H. Gravitational decoherence. *Class. Quantum Gravity* **34**, 193002 (2017).
137. Moore, G. T. Quantum theory of the electromagnetic field in a variable-length one-dimensional cavity. *J. Math. Phys.* **11**, 2679–2691 (1970).
138. Sanz, M., Wieczorek, W., Gröblacher, S. & Solano, E. Electro-mechanical Casimir effect. *Quantum* **2**, 91 (2018).
139. Macrì, V. et al. Nonperturbative dynamical Casimir effect in optomechanical systems: vacuum Casimir–Rabi splittings. *Phys. Rev. X* **8**, 011031 (2018).
140. Wallucks, A., Marinković, I., Hensen, B., Stockill, R. & Gröblacher, S. A quantum memory at telecom wavelengths. *Nat. Phys.* **16**, 772–777 (2020).
141. MacCabe, G. S. et al. Nano-acoustic resonator with ultralong phonon lifetime. *Science* **370**, 840–843 (2020).
142. Tsaturyan, Y., Barg, A., Polzik, E. S. & Schliesser, A. Ultracoherent nanomechanical resonators via soft clamping and dissipation dilution. *Nat. Nanotechnol.* **12**, 776–783 (2017).
143. Fang, K., Matheny, M. H., Luan, X. & Painter, O. Optical transduction and routing of microwave phonons in cavity–optomechanical circuits. *Nat. Photon.* **10**, 489–496 (2016).
144. Zivari, A., Stockill, R., Fiaschi, N. & Gröblacher, S. Non-classical mechanical states guided in a phononic waveguide. Preprint at <https://arxiv.org/abs/2108.06248> (2021).
145. Marquardt, F., Chen, J. P., Clerk, A. A. & Girvin, S. M. Quantum theory of cavity-assisted sideband cooling of mechanical motion. *Phys. Rev. Lett.* **99**, 093902 (2007).
146. Thompson, J. D. et al. Strong dispersive coupling of a high-finesse cavity to a micromechanical membrane. *Nature* **452**, 72–75 (2008).
147. Law, C. K. Interaction between a moving mirror and radiation pressure: a Hamiltonian formulation. *Phys. Rev. A* **51**, 2537–2541 (1995).
148. Nunnenkamp, A., Børkje, K. & Girvin, S. M. Single-photon optomechanics. *Phys. Rev. Lett.* **107**, 063602 (2011).
149. Rabl, P. Photon blockade effect in optomechanical systems. *Phys. Rev. Lett.* **107**, 063601 (2011).

Acknowledgements

S.B. acknowledges funding by the Natural Sciences and Engineering Research Council of Canada (NSERC) through its Discovery Grant, funding and advisory support provided by Alberta Innovates through the Accelerating Innovations into CarE (AICE)—Concepts Program, and support from Alberta Innovates and NSERC through an Advance Grant. A.X. acknowledges funding by the European Union’s Horizon 2020 research and innovation programme under grant agreement 732894 (FET Proactive HOT) and by the Julian Schwinger Foundation project grant JSF-16-03-0000 (TOM). S.G. is supported by the European Research Council (ERC Starting Grant Strong-Q, 676842; and ERC Consolidator Grant Q-ECHOS, 101001005) and by the Netherlands Organization for Scientific Research (NWO/OCW) as part of the Frontiers of Nanoscience program, as well as through Vidi (680-47-541/994) and Vrij Programma (680-92-18-04) grants. M.P. is supported by the H2020/FETOPEN/2018/2020 project TEQ (766900), the DfE-SFI Investigator Programme (15/IA/2864), COST Action CA15220, the Royal Society Wolfson Research Fellowship (RSWF/R3/183013), the Royal Society International Exchanges Programme (IEC/R2/192220), the Leverhulme Trust Research Project Grant (RGP/2018/266), the UK EPSRC (project QuamNESS, grant EP/T028106/1) and the CNR/RS (London) project “Testing fundamental theories with ultracold atoms”. C.A.R. acknowledges funding by the US National Science Foundation under grant 1125844 and a Cottrell FRED Award from the Research Corporation for Science Advancement under grant 27321. E.M.W. acknowledges funding by the European Union’s Horizon 2020 research and innovation program under grant agreement 732894 (FET Proactive HOT), the German Federal Ministry of Education and Research (contract 13N14777) within the European QuantERA co-fund project QuaSeRT, and project QT-6 SPOC of the Baden-Württemberg Foundation.

Author contributions

All authors contributed to the writing, editing, and revision of the manuscript.

Competing interests

The authors declare no competing interests.

Additional information

Correspondence should be addressed to Shabir Barzanjeh or André Xuereb.

Peer review information *Nature Physics* thanks James Millen and the other, anonymous, reviewer(s) for their contribution to the peer review of this work.

Reprints and permissions information is available at www.nature.com/reprints.

Publisher’s note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

© Springer Nature Limited 2021