





6th International Congress on

"Science and Technology for the Safeguard of Cultural Heritage in the Mediterranean Basin"

PROCEEDINGS

VOL. II - Session B

Diagnostics, restoration and conservation



Athens, Greece 22 – 25 October 2013

© Editore VALMAR – Roma Printed by Centro Copie l'Istantanea, Roma, 2014 ISBN 978-88-97987-04-8

Publishing coordination, revision and realization: Angelo Ferrari - CNR, Inst. of Chemical Methodologies, Italy;

Digital Editing and Data Processing: Stefano Tardiola and Gianni Pingue - CNR, Inst. of Chemical Methodologies, Italy;

Secretariat: Enza Sirugo - CNR, Inst. of Chemical Methodologies, Italy; Manuela Manfredi, A.I.C. Secretariat, Italy.

NANOSTRUCTURED MATERIALS FOR PROTECTION AND CONSOLIDATION OF ANCIENT STRUCTURES

Di Salvo Santina¹

¹Department of Architecture of University of Palermo, Palermo, Italy, santina.disalvo@unipa.it

Keywords: Protection, Consolidation, Conservation, Nanomaterials, Ancient structures, Cultural heritage.

ABSTRACT

The preservation and appreciation of the built cultural heritage is of particular interest, through researches and studies on innovative technologies. As evidenced by the good results obtained in some interventions both at national and international level, activities for the conservation of cultural heritage must be the result of synergies and collaboration of interdisciplinary groups, science and knowledge: architecture, engineering, technology, sociology, economics, urban planning, legislation must be managed and planned to work together. The theme of protection and consolidation of ancient structures, applying non-traditional technologies, requires a comprehensive overview of strategies for reliable interventions and a methodology to achieve goals that are consistent with the concept of sustainability. If sustainability ultimately means learning to think and act in terms of guaranteeing the prosperity of interdependent natural, social, and economic systems, then the built heritage, with its unique values and experiences must be contextualized and integrated with this view.

In fact, conservation science is one of the most complex topics in the materials science as it requires expertise ranging from the history of art and archaeology to the advanced analytical and physical chemistry. However, the recent development has shown that the complex tasks of the conservation of the cultural heritage can be solved very effectively using novel nanomaterials and nanotechnology procedures. The aim of this study is to evaluate the effectiveness of inorganic compatible treatments, based on nanoparticles as consolidants for wood and stone materials affected by different kinds of decay. Scientific experiences of the Author of the present contribution were carried out, as shown by a new scientific and technological patent, regarding the implementation projects on nanomaterials, mainly on nanostructured inorganic oxides, and more particularly titanium sesquioxide (Ti2O3) and silicon (Si2O3). All the results converged in individuating these nanometric particles as an innovative, with a high level of biocompatibility, and efficient material for the consolidation of architectural wood and stone surfaces.

INTRODUCTION

The present paper addresses to the latest innovations concerning nanostructured-materials, highlighting the issue on methods for selecting most appropriate strategies and tools to achieve the recovery of identity and sustainability of interventions in the ancient built heritage, both at national and European level [1]. The last decade has witnessed an exponential growth of research activities based on studies on the preservation and appreciation of the ancient structures of cultural heritage, particularly of ancient stone and wood. The theme of recovery of old buildings, applying non-traditional technologies, requires, in particular, a methodology to achieve goals that nowadays are consistent with the concept of sustainability. Recently, sustainability has evolved as a significant mode of thought in nearly every field of intellectual activity [2].

In this context, the protection and appreciation of the ancient materials like wood and stone, is of particular interest, expecially through new technologies. Innovative technologies and, in particular, nanotechnology are multidisciplinary issues involving various research topics: from molecular biology tochemistry, from materials science to physics, and engineering [3].

Therefore, activities for the conservation of built heritage must be the result of synergies and collaboration of multiple groups, science and knowledge: architecture, engineering, technology, sociology, economics, urban planning, legislation must be managed and planned to work together. In fact, if sustainability ultimately means learning to think and act in terms of guaranteeing the prosperity of interdependent natural, social, and economic systems, then the built cultural heritage, with its unique values and experiences must be contextualized and integrated with this perspective [4].

We know that decisions concerning conservation of the built environment have in the past been the domain largely of architectural historians, urban planners, conservation specialists, and related professionals. Actually, conservation cannot remain a closed and solely self-referential profession, and indeed it has not [5]. With particular regard to the conservation of historic neighbourhoods and city centres, as well as individual monuments and sites of unique beauty, the challenge facing the conservation community is to develop a set of strategies and priorities that will permit it to focus its efforts on the conservation of those resources where the benefit-cost ratio is most favorable [6].

In this case sustainability means controlling change and choosing directions that capitalize most effectively on the inheritance from the past. In any decision about change and about the impact of the future on the remains of the past, therefore we should be conscious of two separate questions: the first is how to reconcile minimizing loss with the needs of the present; the second is how to ensure that the balance we strike does not reduce too greatly our successor's options for understanding and enjoying their inheritance.

Actually, built environment and heritage conservation should provide a dynamic vehicle by which individuals and communities can explore, reinforce, interpret and share their historical and traditional past and present, through community membership as well as through input as a professional or non-professional affiliate [7].

RESULTS - PATENTS AND EXPERIMENTATIONS

The use of innovative technologies can be a test and a challenge for the re-construction of the rules of the upgrade and the ancient built and buildable landscape, by inserting the environmental variable and the resulting constructive solutions [8]. The joint approach of different disciplines is a strength of the methodology of the project, where a large number of transversal phases can allow research groups to join in the development of activities that are useful to compare experiences and adopt patterns of success [9].

Fundamental understanding of synthesis, processing and characterisation of functional nanosystems can render exceptional opportunities for their technological transformation to real applications. The dissemination of knowledge on nanotechnology, nanomaterials and their use is now a necessary step by considering the enormous potential applications that nanotechnologies offer in terms of materials development, techniques and uses. Including both new construction and Cultural Heritage, nanotechnology is providing a significant input to innovation in processes and products. There are numerous research studies and experimentations relating to technological innovation for the preservation and appreciation of the ancient built heritage.

In particular, the deterioration of stone and wood with which the ancient structures and monuments are built is a complex physical-chemical process caused by the interaction of several factors: climate of the locations, urban pollution, and the same material properties. Every direct method to consolidate and, more particularly, to protect and conserve the ancient

structures must have the following characteristics: a) to be respectful of the environment; b) to be careful not to damage the wood surfaces or stone material of the ancient structures; c) not to affect the structural characteristics of the material that forms the structure to be preserved; d) to be well absorbed by capillarity; e) not to produce any change of colour of the treated material; f) to have a good penetration and ensure a high degree of consolidation. Scientific experiences of the Author of the present contribution, shown by scientific and technological patents, regarding the implementation projects on nanomaterials, nanostructured inorganic oxides, and more particularly titanium sesquioxide (Ti2O3) and silicon (Si2O3), have demonstrated that it is possible to obtain materials with a high level of biocompatibility that can be used for the consolidation of archaeological wood and stones. One of the most promising inorganic compounds for the consolidation of these materials is lithium silicate.

At the state of the art, two patented inventions in the United States, respectively US n. 4.443.496 (Obitsu et al., Application No. 400,820) and US n. 4.521.249 (Obitsu et al., Application No. 567,028), claim the use of lithium silicate to impregnate concrete surfaces. The first invention (1984) is titled *Agent and method for modifying surface layer of cement structures* and the second invention (1985) is titled *Silicate containing agent cement surface modified with this agent*. The descriptions of said patents highlight a method for the formation of a silicate coating on the surface of concrete. Actually, the inventions claimed by the abovementioned U.S. patents do not address the problem of consolidation and conservation of stone, of which the pH is much lower than the matrix of cement. The patents provide for the use of a plasticizer which is sodium salt of naphthalene-sulfonate condensed with formaldehyde. This polymer has a typical dark brown colour and its application produces an undesirable colour formation of substrate (brown staining). Furthermore, the introduction of said organic material produces a microbial infestation of the stone.

Currently, the research aims to constantly create new materials capable of consolidating structures of stone and wood of ancient buildings, without generating any of the aforementioned problems.

The new patent, invented in 2011 and entitled *Innovative sonochemical process that employs ultrasonic cavitation for the synthesis of mono-dispersed amorphous silicon dioxide nanoparticles, and a method for producing high-performance water-soluble lithium silicate compounds, for the application in the consolidation in situ of ancient stone and wood structures* (Di Salvo S., Patent Pending PA2011A000012), represents a powerful breakthrough in the synthesis of new materials for the protection of buildings, therefore for the improvement of the built environment.

This invention relates to a process for synthesizing amorphous nanoparticles and mono-dispersed of silicon dioxide (SiO2), and a method for preparing a compound water-soluble inorganic compound of lithium silicate by reaction, in water, of lithium hydroxide and/or carbonate with said nanoparticles and mono-dispersed of silicon dioxide. Process and method are in place through the use of ultrasonic energy with a frequency between 10 kHz and 100 kHz. That compound of high-performance lithium silicate is applied *in situ* for the consolidation of ancient stone and wooden structures.

In particular, the innovation of the present invention is that of creating economically and conveniently nanoparticles of silicon dioxide, through a new process of synthesis which employs ultrasonic cavitation, totally unknown in the state of the art of science and technology. Ultrasonic cavitation is the energetic effect which is basically used by ultrasound. To be more precise, the ultrasonic cavitation is a physical phenomenon consisting in the creation of *vacuum*

"tears" commonly referred to as "bubbles" in a fluid which immediately and violently implode. This compound of silicon dioxide in nanoscale structure can subsequently react with lithium hydroxide and/or carbonate, in water, to form a specific inorganic material of high-performance having new characteristics. The nanoparticles of silicon dioxide have a crucial role in the creation of a new form of water-soluble lithium silicate, to be applied *in situ* improving the performance of stone and wood materials of ancient structures, essential for a lot of applications in numerous fields of technology. This new material of lithium silicate performs the task perfectly respecting the environment, without changing the physico-chemical and mechanical structures of the treated materials, and all with no lasting effects.

This new process belongs to a field of nanoscience and is directed to the creation and utilization of materials, with dimensions at the molecular level, with features not only greatly improved compared to the traditional ones, but even completely innovative. In fact, the properties and behavior of nanoscale material, obtained according to the teachings of the present invention, provides an opportunity to create inorganic compounds of lithium silicate that operate in a completely different way than those with macro dimensions.

In the following example, it is described an economical method for synthesizing nanoparticles of silicon dioxide, through the use of ultrasonic cavitation and use of sodium silicate as a precursor. Further characteristics and advantages of the object of the present invention will become more apparent through the example of a preferred embodiment, but not exclusive, of the invention, described by way of non-limitative example of the nature of the invention.

PREPARATION OF SILICON DIOXIDE NANOPARTICLES - EXAMPLE

Under the effect of ultrasonic energy at 40 KHz, a solution of concentrated HCl (2.0%) is added dropwise to an aqueous solution of sodium silicate, up to the formation of a colloidal turbid liquid. This precipitate is recovered by filtration and washed, then dried into the oven at 100 ° C for 13 hours and finally calcined in air at 1000 ° C for 40 minutes. The Author of the present invention has found that, for the synthesis of said nanoparticles, very specific parameters must be taken into consideration. These parameters include: ultrasonic cavitation, concentration of sodium silicate and hydrochloric acid concentration.

The nanoparticles, characterized by an average diameter of ~ 20 nanometers (nm), are synthesized through the use of the ultrasonic cavitation that determines the optimal conditions for the formation of molecules with a well-defined, regular spherical structure (Figure 1). More particularly, the Author has found that an adequate ultrasonic frequency is indispensable, in order to avoid the agglomeration of the silicate dioxide nanoparticles. To have an optimum cavitation, capable of generating spherical nanoparticles well-defined of silicate dioxide, this ultrasonic frequency must be between 20 KHz and 60 KHz. In effect, various experiments have shown that a too high ultrasonic frequency could generate the formation of nanoparticles of silicate dioxide characterized by irregular shapes, while a too low ultrasonic frequency could delay the formation of nanoparticles. Others experiments conducted by the Author have demonstrated that a low concentration of HCl is an expedient to avoid the agglomeration of the nanoparticles.

The first step for the synthesis of nanoparticles of silicon dioxide is the release of silicic acid (Si(OH)4) through the hydrolysis of sodium silicate with hydrochloric acid according to the following equation: Na2SiO3 + H2O + 2HCl = Si (OH) 4 + 2NaCl. Subsequently, the silicic acid begins to polymerize with the elimination of the water.

The polymer continues to grow with removal of water forming polymer spheres called primary particles of silicate dioxide, and their magnitude is equal to a few Angstroms (1 Angstrom = 0.1 nanometers or 1x10-10 meters). At some point these primary particles begin to stick to each other through the silanol groups (SiOH) to form silica gel (SiO2), produced in the form of hard granules having the appearance of crystals. The silicic acid condenses rapidly to silicon dioxide with removal of water according to the following reaction: (Si (OH) 4 = SiO2 + 2H2O). Finally, mono-dispersed nanoparticles of amorphous silicon dioxide with diameter of ~ 20 nm and a regular spherical structure are synthesized successfully using only a specific ultrasonic cavitation and sodium silicate as precursor.

In order to achieve the best conditions for synthesizing these nanoparticles, the reaction temperature should be maintained at $40 \,^{\circ}$ C - $50 \,^{\circ}$ C and the ultrasonic frequency of $40 \,^{\circ}$ KHz.

The present invention also includes the method for the preparation of the new compound of water-soluble lithium silicate, which comprises the following steps: a) to pour distilled water in a stainless steel reactor, thermostated and equipped with a sonicator which generates ultrasound; b) to heat the water to a temperature of 60°C; c) to trigger ultrasonic energy characterized by a frequency of 40 KHz and pour a predetermined dose of lithium hydroxide; d) to add in small doses nanoparticles of silicon dioxide (synthesized according to the above example); e) after adding the last amount of silicon dioxide, to raise the reactor temperature up to 70°C; f) when the viscosity of the material contained in the reaction chamber is lowered, to add distilled water and let the solution cool down; g) to take from the reactor the lithium silicate compound (Li2O/SiO2). This water-soluble compound can be used as a hardener, characterized by the unique ability to penetrate by capillary action in the pores, cracks and lesions of structures of stone and wood. The concentration of lithium silicate in the consolidating product ready for use is less than 20 % by weight, while the *ratio* Li2O: SiO2 is in the range 1.0: 1.0 to 1.0: 20.0. The Author of this invention has found that the optimum viscosity of the aqueous solution ready to use lithium silicate should be in the range from 1.8 mPas to 2.5 mPas (megapascal).

CLAIMS AND CONCLUSION

In order to what has been described in detail, the experts in the field can understand that variations in the way of realization of the invention described in the example here shown are possible without thereby alter the technical concepts and/or the essential characteristics of the invention. Therefore, it must be expressly understood that the above example has been proposed only for illustrative and not limitative model of the present invention.

Finally, the invention includes all modifications, additions and substitutions derived from the purpose and spirit of the invention are well declared in the included following claims:

- 1) Sonochemical process that uses ultrasonic cavitation for the synthesis of silica (SiO2) in the form of amorphous mono-dispersed nanoparticles, characterized in that said silicon dioxide is prepared by use of hydrochloric acid (HCl) and sodium silicate as a precursor.
- 2) Process as claimed in Claim 1, characterized in that the hydrochloric acid concentration should be from 0.1% to 5.0%.
- 3) Process as claimed in Claims 1 to 2, characterized in that it uses ultrasonic energy at a frequency between 10 KHz to 100 KHz, and more particularly between 20KHz and 40 KHz.
- 4) Process as claimed in Claims 1 to 3, characterized in that the size of silica nanoparticles can be controlled by varying the frequency of the ultrasonic energy.

- 5) Process as claimed in Claims 1 to 4, characterized in that the mono-dispersed silica nanoparticles have sizes ranging from 1 nm to 100 nm and more particularly from 10 nm to 50 nm.
- 6) Process as claimed in Claims 1 to 5, characterized in that these silica nanoparticles can react with lithium hydroxide and/or carbonate in aqueous solution to obtain water-soluble lithium silicate with nanoscale structure.
- 7) Process as claimed in Claim 6, characterized in that said water-soluble lithium silicate can be applied in situ for the consolidation and protection of stone and wooden of ancient structures.
- 8) Method for preparing a water-soluble inorganic compound of lithium silicate by use of ultrasonic energy having a frequency between 10 kHz and 100 kHz, characterized in that said lithium silicate compound is obtained by reaction, in water, of lithium hydroxide and/or carbonate with silica nanoparticles synthesized according to the above Claims 1 to 5.
- 9) Method as claimed in Claim 8, characterized in that for the preparation of said water-soluble lithium silicate can be used ultrasonic energy having a frequency between 20 KHz and 60 KHz.
- 10) Method as claimed in Claim 9, characterized in that said water-soluble lithium silicate can be present in aqueous solution with a maximum solids content of 40 wt.% and a max viscosity of 20 mPas.
- 11) Method as claimed in Claims 8 to 10, characterized in that the consolidation of natural stones, historic plasters and wooden structures, is produced in situ using an aqueous solution of lithium silicate, whose maximum concentration is less than 20 wt.% and is *characterized* by a Li2O:SiO2 ratio of 1.0: 1.0 20.0.
- 12) Method as claimed in Claims 8 to 11, characterized in that the aqueous solution consisting of lithium silicate has maximum concentration less than 10 wt%.

The consolidating power of water-soluble lithium silicate is highly dependent on the size of the amorphous and mono-dispersed nanoparticles of silicon dioxide. The sonochemical technique, which uses ultrasonic cavitation, has the following advantages in the synthesis of nanoparticles of silicon dioxide: versatility and ease of execution, purity, consistency and high performance of the material obtained. In fact, the self-cleaning ability of this new type of silicon dioxide, having a nanoscale structure, applied directly to the stone and wooden surfaces, allows us to preserve their condition unchanged, without any alterations to their appearance of technical features, preventing biological pollutants and corrosion impurities, effectively counteracting the deterioration of the surfaces of stone materials [10].

This invention, with numerous studies in the field, demonstrate a commitment and interest in the research for innovative materials and the most reliable systems to ensure the consolidation and restoration of ancient structures, significantly reducing maintenance costs. Several lines of research have developed innovative methods and new production processes that allow nanostructured materials to become an advantageous and indispensable component for the preservation, enhancement and appreciation of the ancient built environment. These new nanomaterials can be successfully tested and verified to help bringing history to life, to protect our built environment, setting the stage for a really accessible and safeguarded city in the future.

REFERENCES

[1] Brandon, P. & Lombardi, P., Evaluating Sustainable Development in the Built Environment, Wiley-Blackwell, Oxford, United Kingdom (2011).

416

- [2] Stubbs J. H & Makaš E. G., Architectural conservation in Europe and the Americas, Wiley, Hoboken (2011).
- [3] Pearce J., Albritton S., Grant G., Steed G., & Zelenika I., A new model for enabling innovation in appropriate technology for sustainable development, *Sustainability: Science, Practice, & Policy* 8(2), (2012), 42-53.
- [4] Ayong Le Kama, A. D., Sustainable growth renewable resources, and pollution, *Journal of Economic Dynamics and Control* 25/12 (2001), 1911-1918
- [5] Macinnes, L., Historic Landscape Characterization, in Bishop and Phillips (eds) *Countryside Planning: New approaches to Management and Conservation*, Earthscan, London (2004) 155-169.
- [6] Matero, F. G. & Teutonico, J. M., *Managing change: sustainable approaches to the conservation of the built environment*. 4th Annual US/ICOMOS International Symposium organized by US/ICOMOS, Program in Historic Preservation of the University of Pennsylvania, and the Getty Conservation Institute Philadelphia, 6-8 April 2001.
- [7] Hubbert, M. K, Daniels, F. & Wigner, E. P., Our Energy Resources. Physics Today 2 (April 1949), 19-22.
- [8] Bennet, G., *Cultural Landscape. The conservation challenge in a changing Europe.* Institute for European Environmental Policy, London (1996).
- [9] Fairclough, G., Protecting Time and Space: undestanding historic landscape for conservation in England, in Ucko, P. J. & Layton, R. (eds), *The Archaeology and Anthropology of Landscape: Shaping your landscape*, One World Archaeology 30, Routledge, London (1999), 119-134.
- [10] Di Salvo, S., Methodological approaches for the enhancement of cultural heritage, Aracne, Rome (2012).




Figure 1. Image SEM (Scanning Electron Microscopy). Morphology of the surface of a porous stone sprayed with a 10% solution of lithium silicate which contains nanoparticles of silicon dioxide (\sim 20 nm).

INDEX OF PAPERS

VOLUME I – SESSION A: RESOURCES OF THE TERRITORY

INSTRUMENTS, METHODS, RESEARCH AND PROFESSIONAL TRAINING INITIATIVES FOR CULTURAL HERITAGE TRANSMISSION TO THE FUTURE1
THE ARCHAEOLOGICAL ENSEMBLE OF MÉRIDA AND THE COMPREHENSIVE MANAGEMENT STRATEGY: TOOLS AND METHODS OF CONSERVATION, MAINTENANCE AND VALORIZATION OF A UNESCO SITE
INDOOR MICROCLIMATE AND PRESERVATION OF HISTORIC ARCHITECTURE: THE MALATESTIANA LIBRARY IN CESENA23
INTEGRATED STRATEGIES REGARDING THE REVITALIZATION AND RE-USE OF HISTORICAL CENTRES - CASE STUDY IOSEFIN NEIGHBOURHOOD, TIMISOARA, ROMANIA
THE REHABILITATION AND RE-FUNCTIONALIZATION OF FORTIFIED CITADELS AS PART OF THE REVITALIZATION STRATEGY OF HISTORICAL CENTERS—CASE STUDY ARAD FORTRESS, ROMANIA
THE USE OF WROUGHT IRON IN THE STRUCTURAL SYSTEM OF OTTOMAN BUILDINGS IN TURKEY51
REHABILITATION THROUGH A HOLISTIC CONSERVATION AND REVITALIZATION STRATEGIES FOR THE CITIES: CUMALIKIZIK VILLAGE AS A CASE
RESTORATION STUDIES AND THE RE-USE OF ORHANELI STONE SCHOOL, BURSA-TURKEY 62
STRATEGY FOR THE INTEGRAL REGENERATION OF A HISTORICAL CENTER. THE CASE OF BEN M'HIDI NEIGHBORHOOD IN ALGIERS69
PLANNING TOOLS FOR HISTORIC CENTERS CONSERVATION IN ITALY, CASE STUDY OF "ORTYGIA" SYRACUSE, ITALY
INTANGIBLE SMART CITY INSIDE TANGIBLE HISTORIC CITY: SMART HERITAGE AS REGENERATION OF EURO-MEDITERRANEAN REALITIES91
TANGIBLE AND INTANGIBLE HERITAGE IN THE MEDITERRANEAN SUSTAINABLE CITY 101
TANGIBLE AND INTANGIBLE HERITAGE IN THE MEDITERRANEAN SUSTAINABLE CITY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY
CULTURAL HERITAGE THROUGH HISTORY AND NATURE CONSERVATION AND RE-USE. THE SCICLI CASE STUDY

FRINGSCAPE: A MEDITERRANEAN CITY IN-BETWEEN URBAN LANDSCAPES AND RURAL LANDMARKS	227
THE ROCK-CUT TOMBS OF NORCHIA (VT): THE STATE OF RESEARCH	235
THE MATERIAL PROPERTIES OF HORASAN MORTARS IN SOME OTTOMAN PUBLIC BATHS IN BURSA-TURKEY	244
THE STRUCTURAL FAILURES OF THE FRIGIDARIUM PART OF THE HISTORICAL OTTOMAN BATHS IN BURSA-TURKEY	250
EXAMINATION OF THE MATERIAL PROPERTIES AND THE CONSTRUCTION TECHNIQUES OF TRADITIONAL OTTOMAN TIMBER HOUSES IN THE CUMALIKIZIK VILLAGE, BURSA-TURKEY	257
THE EFFECTS OF SOLAR RADIATION IN ARCHAEOLOGICAL SITES	263
ROBOARCH: AN AUTONOMOUS ROBOT FOR ANALYSIS AND DOCUMENTATION OF HISTORICAL ARCHITECTURES	
ROBOTIC TOOLS AND SYSTEMS FOR MAN/MACHINE COOPERATION IN UNDERWATER ARCHAEOLOGY	279
ARCHAEOLOGICAL TEXT AND URBAN CONTEXTS: STRATEGIES FOR PROMOTION	284
THE ARCHAEOLOGICAL SITE OF BADIA IN TERRA D'OTRANTO:CONTRIBUTION OF THE GEOPHYSICAL PROSPECTING TO THE RECONSTRUCTION OF THE LANDSCAPE FROM THE LATE ANTIQUITY TO THE MIDDLE AGE	291
THE AGORA OF SEGESTA IN IMMERSIVE VIRTUAL ENVIRONMENTS	299
OBJECT TRACKING FRAMEWORK FOR UAV-BASED SURVEILLANCE OF CULTURAL HERITAGE SITES	308
HIGH RESOLUTION SUBSURFACE IMAGING WITH A HOLOGRAPHIC RADAR MOUNTED ON A ROBOTIC SCANNER	314
RECONFIGURING ANCIENT ARCHITECTURE: THE VILLA ROMANA IN PIAZZA ARMERINA	321
THE HISTORIC LIGHTHOUSES OF MEDITERRANEAN BASIN	327
VOLUME I – SESSION C: BIOLOGICAL DIVERSITY	
STATURE AND BODY SHAPE OF ANCIENT EGYPTIANS FROM THE OLD KINGDOM	337
MAKING PROCESS, CONSERVATION AND HISTORICAL STUDIES OF TEXTILES BY RADIOGRAPHIC ANALYSIS. APPLICATION ON HISTORICAL TEXTILES FROM XV AND XVICENTURY	345
BIOLOGICAL AND MICROCLIMATIC DIAGNOSIS IN CULTURAL HERITAGE CONSERVATION: INTERDISCIPLINARY RESEARCH AT PALATINA LIBRARY IN PARMA	352
ANTHROPOLOGICAL ARCHIVES AND SOCIO-ECONOMIC HISTORY OF POPULATIONS LACKING WRITTEN SOURCES. SOME CASE STUDIES	359
THE HISTORIC CYPRESSES OF THE VIALE DI BOLGHERI: NEED OF AN ORGANIC AND NON- STOP ACTION TO PRESERVE A LIVING MONUMENT	367
MOLECULAR TRACING OF THALASSEMIA IN ANCIENT GREEK HUMAN REMAINS	375
HISTORICAL GARDENS OF CATANIA (SICILY)	380
HISTORICAL GARDENS OF CATANIA (SICILY) PLANTS OF HISTORICAL GARDENS OF MILAZZO (MESSINA, SICILY)	
	388
PLANTS OF HISTORICAL GARDENS OF MILAZZO (MESSINA, SICILY)	388 395

VOLUME II – SESSION B: DIAGNOSTICS, RESTORATION AND CONSERVATION

STRUCTURAL ASSESSMENT AND REHABILITATION OF AN HISTORIC TRADITIONAL MASONRY BUILDING IN ATHENS	
DEGRADATION AND PRESERVATION OF RAMMED EARTH. CASE STUDY OF SPAIN	8
THE HISTORY OF ARCHITECTURE AND THE CONSERVATION OF THE BUILT HERITAGE OF THE ARCHDIOCESE OF CHIETI	22
REINFORCEMENT OF HISTORIC MULTI STOREY BEARING STRUCTURES WITH BRACED METAL TUBES	
SURVEY, RESTORATION AND CONSERVATION OF HISTORICAL BUILDINGS AND MONUMENTS BY USING ROBOTIC SYSTEMS	
NATURAL FIBRES AS REINFORCEMENT OF GYPSUM COMPRESSION LAYERS	52
ANASTILOSIS AND RESTORATION OF GUR-DOKHTAR TOMB, TOMB OF ACHAEMENID (IRAN)	60
CONSERVATION PROBLEMS OF AGHJOTS MONASTIC COMPLEX	67
THE MASTER OF ACCADEMIA: A POWERFUL TOOL FOR DATING STRINGED MUSICAL INSTRUMENTS	
WOODEN DOMES, VAULTED AND FLAT CEILINGS, PARTITION WALLS IN THE SICILIAN CONSTRUCTIVE TRADITION KNOWLEDGE FOR THE SAFEGUARD OF ARCHITECTURE AND TECHNIC	
THE SIROCCO CHAMBERS: PASSIVE COOLING STRUCTURES IN THE XVI CENTURY PALERMO AREA	86
BINDERS FOR RETOUCHING SYSTEMS IN CONSERVATION: AN OVERVIEW AND EXPERIMENTAL TESTS	99
THE USE OF COMBINED CLEANING SYSTEMS FOR THE RESTORATION OF A DETACHED GRAFFITO FROM THE MUSEUM OF PALAZZO BRASCHI IN ROME	108
LACUNA'S TREATMENT RESTORATION AND TECHNOLOGICAL INNOVATION	115
ACOUSTIC IMPROVEMENTS IN A HISTORICAL BUILDING RESTORATION	122
KNOWING THE HISTORY AND THE MODIFICATIONS DURING TIME OF A HISTORICAL BUILDING FOR A CARE FUL ASSESSMENT OF ITS SEISMIC VULNERABILITY	
RESEARCH ON THE SEISMIC BEHAVIOUR AND THE RETROFITTING OF THE BUILDINGS FROM THE BULGARIAN CULTURAL HERITAGE	137
LOCAL SEISMIC RESPONSE ASSESSMENT FOR THE SAFEGUARD OF ITALIAN HISTORICAL ARCHITECTURAL MONUMENTS: THE SITE OF SAN CLEMENTE AL VOMANO CHURCH (TERAMO- ABRUZZO)	148
RISK MANAGEMENT STRATEGY FOR CULTURAL HERITAGE	156
RISK MANAGEMENT STRATEGY FOR CULTURAL HERITAGE	
HISTORICAL PALACES, COMBINED ACTIONS FOR SAFETY EVALUATION AND SEISMIC RETROFITTING. THE ROSATI PALACE AS CASE STUDY FOR RECENTLY DEVELOPED DESIGN	161
HISTORICAL PALACES, COMBINED ACTIONS FOR SAFETY EVALUATION AND SEISMIC RETROFITTING. THE ROSATI PALACE AS CASE STUDY FOR RECENTLY DEVELOPED DESIGN SOLUTIONS	161 167
HISTORICAL PALACES, COMBINED ACTIONS FOR SAFETY EVALUATION AND SEISMIC RETROFITTING. THE ROSATI PALACE AS CASE STUDY FOR RECENTLY DEVELOPED DESIGN SOLUTIONS	161 167 173
HISTORICAL PALACES, COMBINED ACTIONS FOR SAFETY EVALUATION AND SEISMIC RETROFITTING. THE ROSATI PALACE AS CASE STUDY FOR RECENTLY DEVELOPED DESIGN SOLUTIONS	161 167 173 180

ARCHAEOMETRIC INVESTIGATION ON GEOPOLYMERIC BINDERS OF ROMAN WATER WORKS IN VERONA (ITALY) (I CENTURY A.D.)
ANCIENT MARBLES FROM IASOS OF CARIA, MINERALOGICAL AND PETROGRAPHIC CHARACTERIZATION AND PROBLEMS OF CONSERVATION210
NEW DIAGNOSTIC THOUGHT FOR THE QUANTITATIVE DEGRADATION DETECTED ON THE ANCIENT STONE MONUMENTS WHICH WERE RESTORED BY PORTLAND CEMENT
A MULTIDISCIPLINARY APPROACH TO STUDY THE "SKIN" OF BAROQUE BUILDINGS IN SALENTO (PUGLIA,ITALY)
CHARACTERISTICS OF MORTARS OF MOSAICS FROM A ROMAN VILLA IN ANTANDROS ANCIENT CITY, TURKEY229
BIOMINERALIZATION CONSOLIDATION OF DEGRADED FRESCO WALL PAINTINGS BY BACILLUS SPHAERICUS BACTERIA237
RESTORATION AND EXHIBITION OF WALL PAINTINGS OF THE EARLY CHRISTIAN BASILICA "THE RED CHURCH"
EVALUATION OF A ROOF CHANGE IN THE ARIADNE'S HOUSE (POMPEII, ITALY): MICROCLIMATIC MONITORING
OIL OVERPAINTINGS REMOVAL USING ATMOSPHERIC PRESSURE PLASMA
HIGH RESOLUTION LASER IMAGING REMOTELY COLLECTED FROM PAINTED SURFACES: INFORMATION FROM REFLECTANCE AND FLUORESCENCE DATA
ANALYTICAL STUDY OF TWO LACQUER OBJECTS FROM MUSEUM OF FACULTY OF APPLIED ARTS, HELWAN UNIVERSITY, GIZA - EGYPT275
THE EFFECTIVENESS OF LIMONENE EMULSIONS TO REMOVE TERPENOID VARNISHES IN PAINTINGS. EVALUATION BY GAS CHROMATOGRAPHY MASS SPECTROMETRY
OIL WORKS ON PAPER: INVESTIGATING THE EFFECT OF OIL MEDIUM ON THE PAPER SUPPORTS OF WORKS OF ART VIA VOC EMISSION ANALYSIS294
SEARCHING FOR A PROTECTIVE AGENT TO BE USED ON SURFACES OF ACRYLIC PAINTINGS 301
APPLICATION OF MULTISPECTRAL IMAGING TO THE RECOVERY OF THE ORIGINAL ILLUMINATION CONDITIONS OF ANCIENT PAINTINGS IN CLOSED ENVIRONMENT 'THE LIGHT RESTORATION'
APPLICATION OF HYPERSPECTRAL IMAGING FOR THE STUDY OF PIGMENTS IN PAINTINGS 317
DETERIORATION FACTORS INFLUENCING ARCHAEOLOGICAL GLASS WHICH USED FOR MEDICAL PURPOSES APPLIED ON A CASE STUDY FROM ISLAMIC ART MUSEUM- CAIRO-
EGYPT
ANALYTICAL STUDY OF SOME UNPUBLISHED LANTERNS OF THE ISLAMIC ART MUSEUM IN CAIRO "HISTORICAL, ARCHAEOLOGICAL AND ARTISTIC STUDY"
SILICA THIN FILM SYNTHETIZED BY SOL-GEL PROCESS FOR THE PROTECTION OF OUTDOOR ARTISTIC CERAMIC IN ARCHITECTURE
AN OVERVIEW ON APULIAN RED FIGURED POTTERY: FROM MANUFACTURING PROCESSES TO PROVENANCE ISSUES
CHEMICAL-PHYSICAL AND MORPHO-MINERALOGICAL METHODOLOGIES AS TOOLS FOR A FRESH VIEWPOINT ON MEDIEVAL GRAFFITA POTTERY
MULTI-TECHNIQUE APPROACH FOR THE INVESTIGATION OF OPAQUE GLASS FROM POMPEII
SPETTROSCOPIC STUDIES ON ETRUSCAN ARCHAEOLOGICAL FINDINGS
A CONSULTING/PRESERVING MACHINE FOR MANUSCRIPTS: THE MALATESTIANA LIBRARY IN CESENA
LIF DIAGNOSTIC ON WOODEN ARTWORKS: MEASUREMENTS OF PAINTED WOOD CORNERS OF GRAN PODER CANOPY
TREATMENT AND RESTORATION OF ANTIQUE SWORD FROM OTTOMAN PERIOD (13 TH AH/19 TH AD CENTURY) AT THE NATIONAL MILITARY MUSEUM SALADIN CITADEL IN EGYPT 391

ARCHAEOMETRIC INVESTIGATION OF ROMAN RAMS AND HELMETS FROM LEVANZO ISLAND, SICILY - ITALY
USE OF LASERS FOR CLEANING OF PAPER DOCUMENTS AND COINS
NANOSTRUCTURED MATERIALS FOR PROTECTION AND CONSOLIDATION OF ANCIENT STRUCTURES41
DURABILITY OF SELF-CLEANING TIO ₂ -BASED NANOCOATINGS ON HISTORICAL STONE SURFACES418
CLEANING OF VARNISH ON 18TH CENTURY RUSSIAN ICON 'SAINT NICHOLAS' BY MEANS OF ATMOSPHERIC PRESSURE PLASMA
CHALK STONE CONSERVATION WITH HYDROXYAPATITE -A STUDY CASE
SYNTHESIS AND CHARACTERIZATION OF A BIO-INSPIRED CALCIUM OXALATE-SILICA NANOCOMPOSITE FOR STONE CONSERVATION442
USING NANOTECHNOLOGY FOR UPGRADING TRADITIONAL BINDING SYSTEMS450
VOLUME III – SESSION D: MUSEUMS PROJECTS AND BENEFITS
TAKING ADVANTAGES OF AUGMENTED REALITY TECHNOLOGY IN MUSEUM VISITING EXPERIENCE
YOUTH AND CULTURE10
PLANNING THE PRESERVATION TO ENCREASE THE VALUE. THE SOUT-WESTERN SUBURB OF ROME, RIVER TEVERE DELTA AND OSTIA AND PORTUS ARCHAEOLOGICAL PLACES
THE MUSEUM OF LONDON, A CITY MUSEUM AS NARRATIVE EXHIBITION28
SOFTWARE FOR STORAGE, MANAGEMENT AND ANALYSIS OF PHYSICAL PARAMETERS: CULTURAL HERITAGE MONITORING38
DEVELOPMENT OF VIRTUAL ENVIRONMENTS FOR THE MUSEUM COMMUNICATION4
ONLINE CONTENT-BASED RETRIEVAL AND FRUITION WITH MULTIWORDNET: AN EXPERIMENTATION
AN ECOMUSEUM ICON OF THE MEDITERRANEAN IN THE ETNA VULCANO AREA58
RELIGIOUS ITINERARIES IN SICILY: AN EURO-MEDITERRANEAN ROUTE INSPIRED BY THE CULT OF ST. AGATHA
ECO-MUSEUMS AND LANDSCAPE PLANNING IN ITALY74
VOLUME III - SESSION E: CULTURAL HERITAGE IDENTITY
MULTIDISCIPLINARY INTEGRATED STUDY OF SAINT ILDEPHONSE'S COLLEGE, UNIVERSITY OF ALCALÁ (MADRID, SPAIN)
R&D FOR THE CULTURAL HERITAGE AS AN INNOVATION POLICY: THE INFORMATION SYSTEM ON THE SKILLS AND SCIENTIFIC RESULTS OF THE NATIONAL RESEARCH COUNCIL OF ITALY
ARCHITECTURAL ANALYSIS OF THE ANTEZANA HOSPITAL: A 15 TH CENTURY NOBLE HOUSE IN THE HISTORIC CITY OF ALCALÁ DE HENARES (MADRID, SPAIN)
INDUSTRIAL HERITAGE IN BASILICATA (SOUTHERN ITALY)
3D LASER-COLOURED SCANNING TECHNIQUE FOR AUTOMATIC FRESCOS DEFECTS DETECTION119
PRESERVE AND VALUE. THE DIGITAL PLATFORM FOR THE ARCHAEOLOGICAL SITE OF OSTIA AND PORTUS
FROM HERITAGE BUILDING DIGITIZATION TO COMPUTERIZED EDUCATION

DOCUMENTATION	
CLAN - CULTURAL LOCAL AREA NETWORK; A PROJECT FOR VALORIZATION AND CONSERVATION OF TERRITORY'S WIDESPREAD CULTURAL HERITAGE	
HISTORICAL PLACE NAMES: FROM ARCHIVES TO LINKED OPEN DATA	158
ADVANCED INFORMATIC METHODOLOGIES APPLIED TO THE CULTURAL HERITAGE: 3D RECONSTRUCTION OF THE ST. ANGELO DI CIVITELLA DI NESCE COMPLEX (RIETI, ITALY)	
DIASPORA AND SURROUNDINGS-METHODOLOGY FOR RESEARCH REGARDING ISSUES OF IDENTITY AND GLOBALIZATION	
GIS-BASED ARCHAEOLOGICAL RECORDING IN LEBANON	. 187
EXTRACTING INFORMATION FROM MULTIMODAL IMAGES OF DOCUMENTS AND ARTWORKS	. 196
THE ACTIVITY OF CEN TC 346-CONSERVATION OF CULTURAL HERITAGE	205
ASSESSMENT OF FUNERARY MONUMENTS STONE DECAY IN SAINT ANTHONY BASILICA IN PADOVA	
'SIRACUSA 3D REBORN'. AN ANCIENT GREEK CITY BROUGHT BACK TO LIFE	220
THE DIGITAL STEREO-ORTHOIMAGE: A TECHNIQUE FOR OPTIMAL GEOMETRIC DOCUMENTATION OF COMPLEX ARCHAEOLOGICAL MONUMENTS	
MENSALE: MENSE STORICHE ED ARTISTICHE LUCANE. BETWEEN ART AND ALIMENTATION	. 237
HISTORIC CELLARS OF BASILICATA, THE "CINTI" OF GRASSANO	248
RFID TECHNOLOGY FOR THE MANAGEMENT OF NATURAL HISTORY COLLECTIONS	259
BUILDING AN OPEN SOUND ARCHIVE: THE CASE OF THE GRA.FO PROJECT	264
RIO DE JANEIRO, ROME AND THE MEGA EVENTS: COMPARING MODELS OF URBAN DEVELOPMENT	
THE SERCHIO VALLEY AS A NEW TOURIST DESTINATION IN TUSCANY. A CASE HISTORY	275
INTERDISCIPLINARY STUDY OF THE PRESERVATION STATE AND CONSERVATION PROCEDURES OF THE EARLY CHRISTIAN BASILICA IN THE SANCTUARY OF APOLLO ERETHIMIOS IN THEOLOGOS, RHODES	1
MEDIEVAL HISTORICAL LANDSCAPE AND ARCHITECTURE ALONG THE CULTURAL ROUTES IN THE NORTH-WEST OF ITALY	
PROBLEM - BASED METHODOLOGY IN BUILT HERITAGE PROTECTION - A PARADIGM FOR BUILDING MATERIALS'DECAY DUE TO ACID RAIN	
APPLICATION OF INTEGRATED DOCUMENTATION PROTOCOLS IN VILLA KLONARIDIS (HISTORIC BUILDING)	. 315
"HANDS-ON CULTURAL HERITAGE" EDUCATIONAL APPROACH INTERCONNECTING SECONDARY WITH TERTIARY LEVEL EDUCATION	
NEW MEDIA AND CULTURAL HERITAGE	. 335
BEYOND THE FRINGE: A REFLECTION ON AGRO-FOREST SYSTEMS, LANDSCAPE AND SOCIETY IN MEDITERRANEAN PERI-URBAN AREAS	
VOLUME III – SESSION F: CULTURAL ASSETS AS RESOURCES AND SUSTAINABLE DEVELOPMENT	
ITALIAN CULTURAL HERITAGE: REFLECTIONS AND PERSPECTIVES OF THE UNESCO SITES WITHIN THE NATIONAL TOURISM SYSTEM	
THE NEW MANAGEMENT APPROACH IN PROTECTION AND REACTIVATION OF CULTURAL AND NATURAL HERITAGE IN RESAVA-MLAVA REGION	

THE SUSTAINABLE DEVELOPMENT OF A TRADITIONAL SETTLEMENT: THE CASE OF DRAKOPOULATA SETTLEMENT AS A MODEL OF CULTURAL, ECONOMICAL & TOURIST VIABLE UNIT	
INTEGRATED MANAGEMENT OF CULTURAL HERITAGE AND ACTIVITIES IN THE MEDITERRANEAN COUNTRIES: AN INTEGRATED CULTURAL SYSTEM	
BUILT HERITAGE IN GREEK INSULAR REGIONS: THE CASE OF CASTLES IN THE IONIAN ISLANDS	
PRINCIPLES OF SPATIAL PLANNING FOR SUSTAINABLE DEVELOPMENT: CREATING AREAS OF OPEN-AIR MUSEUM IN MANI	
PROPOSAL FOR A TYPOLOGICAL, TOPOGRAPHICAL AND MORPHOLOGICAL ATLAS OF QANAT	405
'MU.S.A. – MUST SEE ADVISOR' PROJECT: A CULTURAL HERITAGE BOOSTER	410
TELL TUQAN: GRAPHIC DESIGN, COMMUNICATION AND ENHANCEMENT	420
THE VICUS OF CALVATONE-BEDRIACUM: CULTURAL HERITAGE PROMOTION AND COMMUNICATION	