



Frontiers International Conference
on Wastewater Treatment



PROCEEDINGS
Frontiers International Conference on
Wastewater Treatment (FICWTM)

May 21–24, 2017

Palermo, Italy



Frontiers International Conference
on Wastewater Treatment



PROCEEDINGS
Frontiers International Conference on
Wastewater Treatment (FICWTM)

May 21–24, 2017

Palermo, Italy

**Proceedings of Frontiers International Conference on Wastewater
Treatment
May 21-14, 2017, Palermo, ITALY.**

How to cite the full proceedings:

Mannina, G., 2017. Proceedings of Frontiers International Conference on
Wastewater Treatment
May 21-14, 2017, Palermo, ITALY.

How to cite an individual paper:

Author, A., Author, B., Author, C..., 2016. This is the title of your paper. In:
Mannina, G., 2017. Proceedings of Frontiers International Conference on
Wastewater Treatment
May 21-14, 2017, Palermo, ITALY.

Peer Review:

Each paper has been peer reviewed by at least three independent reviewers
with possible outcomes of reject, revise, and accept.



Comparison of two mathematical models for greenhouse gas emission from membrane bioreactors

G. Mannina*, A. Cosenza*

*Dipartimento di Ingegneria Civile, Ambientale, Aerospaziale, dei Materiali, Università di Palermo, Viale delle Scienze, Ed. 8, 90100, Palermo, Italy.

(giorgio.mannina@unipa.it; alida.cosenza@unipa.it)

Summary

In this study two mathematical models (Model I and Model II), able to predict the nitrous oxide (N_2O) and carbon dioxide (CO_2) emission from an University Cape Town (UCT) – membrane bioreactor (MBR) plant, have been compared. Model I considers the N_2O production only during the denitrification. Model II takes into account the two ammonia-oxidizing bacteria (AOB) formation pathways for N_2O . Both models were calibrated adopting real data. Results highlight that Model II had a better capability of reproducing the measured data especially in terms of N_2O model outputs. Indeed, the average efficiency related to the N_2O model outputs was equal to 0.3 and 0.38 for Model I and Model II respectively.

WWTP; N_2O modelling; nutrient removal; greenhouse gases.

Introduction

During the last years, the attention on wastewater treatment plants (WWTPs) as sources of greenhouse gases (GHGs) (e.g., carbon dioxide, CO_2 , nitrous oxide, N_2O , and methane, CH_4) has considerably increased. Among the GHGs produced by WWTPs, N_2O is the most environmentally hazardous due to its strong global warming potential (GWP) (298 higher than CO_2) and its capacity to deplete the stratospheric ozone layer (IPCC, 2007).

An accurate quantification and mitigation of N_2O emissions is imperative for an environmental protection. With this regard, the adoption of mathematical models allows to select designing or operating choices aimed at reducing the total amount of GHG emissions from WWTPs.

Several efforts have been performed in literature for establishing the best tool to predict/quantify GHG (Mannina et al., 2016; Spérandio et al., 2016; Pocquet et al., 2016). However, the N_2O estimation is still the major crucial aspect in GHG modelling since its formation mechanisms are still under review (Ni et al., 2015). Current knowledge on N_2O emissions suggests that it can be produced both during nitrification and denitrification processes (Kampschreur et al., 2011). Furthermore, autotrophic ammonia-oxidizing bacteria (AOB) can contribute to N_2O production by means of two pathways: i. the nitrifier denitrification (ND) pathway, where N_2O represents the terminal product of nitrite reduction (Law et al., 2012); ii. the incomplete hydroxylamine (NH_2OH) oxidation (NN) pathway, where N_2O is an intermediate product during the NH_2OH oxidation (Pocquet et al., 2016). With this regard, literature suggests that mathematical models that include both AOB contribution pathways reproduce well the measured data (Peng et al., 2015). However, this knowledge has been acquired on conventional activated sludge systems (CAS) often using short-term data (Ni et al., 2013b). Very few studies have been performed for integrated membrane bioreactor (MBR) models where physical separation processes and biological processes affecting the membrane fouling (e.g., soluble microbial products – SMP – formation/degradation) have to be included jointly. Specifically, Mannina and Cosenza (2015) have proposed an integrated ASM2d–SMP–GHG model (Model I) able to predict the N_2O and CO_2 emission from an University Cape Town (UCT) – MBR plant. Mannina and Cosenza (2015) consider the N_2O production only during the denitrification according to the approach of Hiatt and Grady (2008).



A new integrated MBR model including the two AOB formation pathways for N_2O has been recently proposed by Mannina and Cosenza (2017) (namely, ASM2d-SMP-GHG-2P-AOB) (Model II). The purpose of this study was to compare the two models (i.e., Model I and Model II) for GHG emissions from MBR.

Material and Methods

Mathematical models description. Both Model I and Model II are divided in two sub-models (physical and biological). The physical sub-model describes the key processes occurring during membrane physical separation, including membrane fouling (involving 6 model factors and 2 state variables). Regarding, the biological sub-models they are based both on the ASM2d and they include the SMP formation/degradation processes (Jiang et al., 2008; Henze et al., 2000). Furthermore, both models take into account CO_2 as state variable according to the continuity-based model interface as proposed by Vanrolleghem et al. (2005). Despite the aforementioned similarities, the biological sub-models are deeply different. Indeed, Model I employs the Hiatt and Grady (2008) approach for N_2O . Consequently, Model I considers the two-step nitrification process (involving AOB and nitrite oxidizing bacteria, NOB) and the four step denitrification process. Furthermore, the N_2O is modelled as an intermediate product during the heterotrophic denitrification (see further details in Mannina and Cosenza, 2015). Conversely, Model II considers the N_2O formation due both to heterotrophic and autotrophic biomass. In particular, regarding the autotrophic, Model II describes N_2O formation during nitrification combining the two major AOB formation pathways, according to the approach presented by Pocquet et al. (2016). In Model II, N_2O formation during the heterotrophic denitrification is described as in Model I.

Finally, regarding the stripping of N_2O and CO_2 gas both Model I and II employ an algorithm based on the diffusion coefficients (Mannina and Cosenza, 2015). Model I involves 24 state variables and 109 model factors (stoichiometric, kinetic, fractionation and physical factors). While, Model II involves 25 state variables and 116 model factors.

Models application and calibration. Each model has been applied to a pilot plant with a UCT-MBR scheme treating $20 L h^{-1}$ of real wastewater. For the models calibration an innovative calibration protocol was employed (Mannina et al., 2011). This innovative calibration protocol is based on a step wise calibration with respect to a group of model outputs. With this regard, model calibration has been carried out considering a long term monitoring data set. The selection of the model factors to be calibrated has been performed by applying the Standardized Regression Coefficient (SRC) method (Saltelli et al., 2004).

Criteria for comparison. Both models were compared by calculating model efficiencies on the basis of measured and simulated data. Specifically, it has been calculated the efficiency of each model output (E_i) (exponential equation, E_{exp}) and the total model efficiency (E_{MOD}) (Mannina et al., 2011). Four coefficients have been adopted to quantify the goodness of model response: E_{exp} , the root mean squared error (RMSE), the Nash and Sutcliffe efficiency (N&S) (Nash and Sutcliffe, 1970) and the determination coefficient, R^2 .

Results and Discussion

For sake of conciseness, only the results related to the N_2O model outputs (both dissolved and off-gas concentration within each reactor of the UCT-MBR pilot plant) will be here presented and discussed.

Figure 1.1a shows the results of the average, maximum and minimum efficiency (calculated adopting the exponential expression) obtained during the calibration process for



the dissolved and off-gas N_2O model outputs and for each model. Figure 1.1b shows the total model efficiency (E_{MOD}) and the average efficiency for both models in terms of N_2O . A general improvement of the efficiency of the dissolved N_2O model outputs for non-aerated reactors (anaerobic and anoxic) and MBR has been obtained for the Model II (Figure 1.1a). While, similar results were obtained in terms of Off-gas N_2O model outputs (Figure 1.1a). Data of Figure 1.1b confirm the general improvement of the calibrated Model II (respect to Model I) in terms of N_2O model outputs. Indeed, the average model efficiency of the N_2O model outputs increased from 0.3 (Model I) to 0.38 (Model II) (see, Figure 1.1.b).




Figure 1.1 Average, maximum and minimum efficiency (exponential expression) for dissolved and off-gas N_2O model outputs for each reactor and model (a); total model efficiency and average efficiency (exponential expression) for dissolved and off-gas N_2O model outputs related to the calibrated model (b)

For sake of completeness in Figure 1.2 the measured versus simulated data for both dissolved (Figure 1.2a) and off-gas N_2O (Figure 1.2b) in each reactor of the pilot plant are shown. A slight overestimation of simulated data occurred for the two models, expecting some cases, both for dissolved and off-gas N_2O . This result is likely debited to the discrete sampling. Continuous sampling would likely improve the results.




Figure 1.2 Measured versus simulated data for calibrated Model I and Model II related to the Dissolved (a) and Off-gas N₂O (b).

Table 1.1 summarizes the results of the four coefficients adopted for evaluating the two models. Data of Table 1.1 confirm the general improvement of the results for Model II (respect to Model I) for N₂O state variables for each estimated coefficient.

Table 1.1 Values of the coefficients adopted for comparison between Model I and Model II

Model	Coefficient	Dissolved N ₂ O					Off-gas N ₂ O				E _{MOD}
		Anaer	Anoxic	Aerobic	MBR	Perm	Anaer	Anoxic	Aerobic	MBR	
I	E _{exp}	0.37	0.38	0.36	0.3	0.29	0.27	0.39	0.39	0.35	0.55
	N&S	-0.3	-0.06	-0.34	0.63	-1.17	-0.3	-0.09	-0.11	-0.15	
	R ²	0.37	0.02	0.02	0.12	0.39	0.08	0.02	0.02	0.012	
	RSME	0.013	0.009	0.009	0.01	0.013	0.021	0.014	0.013	0.014	
II	E _{exp}	0.32	0.43	0.32	0.4	0.27	0.29	0.4	0.39	0.45	0.56
	N&S	-0.13	0.04	-0.59	-1.16	-1.54	-0.16	0.26	-0.06	0.2	
	R ²	0.08	0.57	0.1	0.34	0.15	0.04	0.71	0.02	0.25	
	RSME	0.013	0.008	0.01	0.012	0.014	0.02	0.011	0.012	0.012	

Conclusions

Two integrated MBR models which include GHGs as state variables have been compared. The two models mainly differ for the description of N₂O production processes: Model I considers the N₂O production only during denitrification; Model II, more detailed than Model I, considers the contribution of autotrophic biomass during N₂O production considering both the ND and NN pathway. Model results showed a better capability of Model II in reproducing the measured data.

Acknowledgments

This work forms part of a research project supported by grant of the Italian Ministry of Education, University and Research (MIUR) through the Research project of national interest PRIN2012 (D.M. 28 dicembre 2012 n. 957/Ric – Prot. 2012PTZAMC) entitled “Energy



consumption and GreenHouse Gas (GHG) emissions in the wastewater treatment plants: a decision support system for planning and management – <http://ghgfromwwtp.unipa.it>” in which the first author is the Principal Investigator.

References

- Henze, M., Gujer, W., Mino, T. & Van Loosdrecht, M. 2000 Activated sludge models ASM1, ASM2, ASM2d and ASM3. In: IWA Task Group on Mathematical Modelling for Design and Operation of Biological Wastewater Treatment. IWA Publishing, London, UK.
- Hiatt, W.C., Grady Jr, C.P.L., 2008. An updated process model for carbon oxidation, nitrification, and denitrification, *Water Environ. Res.* 80, 2145–2156.
- IPCC, 2007. Changes in atmospheric constituents and in radiative forcing. In: Solomon, S. et al. (Eds.), *Climate Change 2007: The Physical Science Basis. Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change*. Cambridge University Press, Cambridge, pp. 114–143
- Jiang, T., Myngheer, S., De Pauw, D.J.W., Spanjers, H., Nopens, I., Kennedy, M.D., Kennedy, M.D., Amy, G., Vanrolleghem, P.A., 2008. Modelling the production and degradation of soluble microbial products (SMP) in membrane bioreactors (MBR). *Water Res* 42(20), 4955–4964
- Kampschreur MJ, Kleerebezem R, de Vet WWJM, van Loosdrecht MCM. 2011. Reduced iron induced nitric oxide and nitrous oxide emission. *Water Research* 45, 5945–5952.
- Law Y, Ni B-J, Lant P, Yuan Z. 2012. N₂O production rate of an enriched ammonia-oxidising bacteria culture exponentially correlates to its ammonia oxidation rate. *Water Research* 46, 3409–3419.
- Mannina, G., Cosenza, A., 2017. A new integrated MBR model including GHG emissions. Submitted to *Environmental Science & Technology*.
- Mannina, G., Ekama, G., Caniani, D., Cosenza, A., Esposito, G., Gori, R., Garrido-Baserba, M., Rosso, D., Olsson, G., 2016. Greenhouse gases from wastewater treatment — A review of modelling tools, *Sci. Total Environ.* 551–552, 254–270.
- Mannina, G., Cosenza, A., 2015. Quantifying sensitivity and uncertainty analysis of a new mathematical model for the evaluation of greenhouse gas emissions from membrane bioreactors. *Journal of Membrane Science* 475, 80–90.
- Mannina, G., Cosenza, A., Vanrolleghem, P.A., Viviani, G., 2011. A practical protocol for calibration of nutrient removal wastewater treatment models. *Journal of Hydroinformatics* 13.4, 575-595.
- Nash J.E. and Sutcliffe J.V. 1970. River flow forecasting through the conceptual model, Part 1: a discussion of principles. *J. Hydro.*10(3), 282-290.
- Ni B-J, Pan Y, van den Akker B, Ye L, Yuan Z. 2015. Full-Scale Modeling Explaining Large Spatial Variations of Nitrous Oxide Fluxes in a Step-Feed Plug-Flow Wastewater Treatment Reactor. *Environmental Science & Technology* 49 9176–9184.
- Peng L, Ni B-J, Ye L, Yuan Z. 2015a. Selection of mathematical models for N₂O production by ammonia oxidizing bacteria under varying dissolved oxygen and nitrite concentrations. *Chemical Engineering Journal* 281, 661–668.
- Pocquet M, Wu Z, Queinnec I, Spérandio M. 2016. A two pathway model for N₂O emissions by ammonium oxidizing bacteria supported by the NO/N₂O variation. *Water Research* 88, 948–959.
- Saltelli, A. Tarantola, S. Campolongo, F. Ratto, M. *Sensitivity analysis in practice. A guide to assessing scientific models*, Probability and Statistics Series, John Wiley & Sons Publishers, Chichester, England, 2004.
- Spérandio M, Pocquet M, Guo L, Ni B-J, Vanrolleghem PA, Yuan Z. 2016. Evaluation of different nitrous oxide production models with four continuous long-term wastewater treatment process data series. *Bioprocess and Biosystems Engineering* 39, 493–510.
- Vanrolleghem, P.A., Rosen, C., Zaher, U., Copp, J., Benedetti, L., Ayesa, E., Jeppsson, U., 2005. Continuity-based interfacing of models for wastewater systems described by Petersen matrices. *Water Sci. Technol.* 52, 493–500.