

Adhesive debonding detection of FRP reinforcement by the ultrasonic non-destructive technique

Emma La Malfa Ribolla¹, Giuseppe Fileccia Scimemi¹, Antonino Spada¹, Giuseppe Giambanco¹

¹ *Department of Civil, Environmental, Aerospace, Materials Engineering, University of Palermo, Italy*

E-mail: emma.lamalfaribolla@unipa.it, giuseppe.filecciascimemi@unipa.it, antonino.spada@unipa.it, giuseppe.giambanco@unipa.it

Keywords: FRP; Ultrasonic; Non-destructive testing.

Fiber reinforced polymer (FRP) composite systems are extensively used for repairing and reinforcing structurally inefficient concrete structures. The performance of an FRP rehabilitation system is highly influenced by its integrity. In particular, the presence of defects, e.g. voids, inclusions, debonds, improper cure and delaminations, caused by an inaccurately manufacture and installation, may affect the capability of the rehabilitated structure. For this reason, non-destructive (ND) methods could be used to assess the quality of the reinforcement [1,2].

In this work an ultrasonic ND technique for detecting delamination defects in FRP reinforcement is presented. The technique couples the Akaike information criterion (AIC), used as automatic starting time signal detection [3] and the equivalent time-length (ETL) of the signal, used as indicator of the energy distribution of the signal with respect to the beginning of the signal [4].

When a perfect bonding between FRP and concrete substrate exists, the acoustical impedance mismatch is small, as both the FRP and the underlying material are dense solids, so the energy is almost transmitted to the concrete. On the other hand, when the adherence between FRP and concrete is compromised by the presence of a thin air gap, the acoustical impedance mismatch is bigger and a great amount of energy is reflected back. The results show that the energetic indicator ETL is particularly sensitive to the quality of the bonding of the FRP-concrete substrate.

The proposed technique has been tested in pitch-catch mode on FRP reinforcements bonded to concrete substrates, both *in vitro*, using samples with imposed well-known defects, and *in situ*, on reinforced concrete beams included in a floor slab.

References

- [1] Dong, Y. and Ansari, F., Non-destructive testing and evaluation (NDT/NDE) of civil structures rehabilitated using fiber reinforced polymer (FRP) composites, *Service Life Estimation and Extension of Civil Engineering Structures*, Karbhari V.M. and Lee L.S. (eds), Woodhead Publishing, Cambridge, page 193-222 (2011).
- [2] Bastianini, F., Di Tommaso, A. and Pascale, G., Ultrasonic non-destructive assessment of bonding defects in composite structural strengthenings, *Composite Structures*, **53**, page 463-467 (2001).
- [3] Kurz, J.H., Grosse, C.U. and Reinhardt, H.W., Strategies for reliable automatic onset time picking of acoustic emissions and of ultrasound signals in concrete, *Ultrasonics*, **43**, page 538-546 (2005).
- [4] Contin, A., Cavallini, A., Montanari, G.C., Pasini, G. and Puletti, F., Digital detection and fuzzy classification of partial discharge signals, *Dielectrics and Electrical Insulation, IEEE Transactions on*, **9**, page 335-348 (2002).